

---

# **LMG0605**

**Halanych**

---

## **Cruise Data Report**

By W. Kevin Pedigo and Dan Elsberg

**May 13 - Jun 14, 2006**

# Table of Contents

<b>INTRODUCTION .....</b>	<b>1</b>
<b>ARCHIVE DATA EXTRACTION .....</b>	<b>2</b>
<b>CD DIRECTORY STRUCTURE .....</b>	<b>3</b>
<b>DISTRIBUTION CONTENTS .....</b>	<b>4</b>
ADCP .....	4
CALIBRATION.....	4
CTD.....	4
<i>CTD/.....</i>	<i>4</i>
<i>CTD/Setup/.....</i>	<i>4</i>
<i>CTD/Scripts/.....</i>	<i>4</i>
<i>CTD/Data/raw.....</i>	<i>4</i>
<i>CTD/Data/process .....</i>	<i>4</i>
ISOBAR CHARTS .....	5
DATA AND SCIENCE REPORT .....	5
SITREP .....	5
SALTS .....	5
OXYGEN.....	6
SCIENCE .....	6
WAYPOINTS.....	6
QC PLOTS .....	6
JGOFS DATA SET .....	6
RVDAS .....	7
<i>Meteorological and Light Data .....</i>	<i>7</i>
<i>Navigational Data.....</i>	<i>7</i>
<i>Geophysical Data.....</i>	<i>8</i>
<i>Oceanographic Data.....</i>	<i>8</i>
<b>DATA FILE NAMES AND STRUCTURES .....</b>	<b>9</b>
LKNU .....	9
LNDS .....	9
LMET .....	9
LTSG .....	10
TSGFL.....	10
LPCO .....	10
LGUV .....	11
SVP1 .....	11

---

LADC .....	12
LASH .....	12
LGYR .....	13
TGPS .....	13
LPCD .....	15
LFLR .....	16
LOXY .....	16
<b>LMG SENSORS .....</b>	<b>18</b>
SHIPBOARD SENSORS .....	18
CTD SENSORS .....	18
<b>ACQUISITION AND PROCESSING INFORMATION .....</b>	<b>19</b>
PROCESSING SPECIFICS.....	19
ERRORS AND EVENTS .....	19

---

## Introduction

The LMG data acquisition systems continuously log data from a suite of instrumentation throughout the cruise. This document describes the format of that data and its location on the distribution CDs. It also contains important information that may affect how this data is processed such as instrument failures or other known problems with acquisition.

The data collected during this cruise is distributed on a CD-ROM written in ISO9660 level-1 format. This data format has very strict requirements on filenames and organization. However, it is readable by virtually every computing platform.

All of the data has been archived with the Unix “tar” command and/or compressed using Unix “gzip” compression. Tar files have a “.tar” extension and Gzipped files have a “.gz” extension. Tools are available on all platforms for uncompressing and de-archiving these formats. On Macintosh, Stuffit Expander with DropStuff will open a tar archive and uncompress gzipped and Unix compressed files. For Windows, WinZip, a shareware utility included on this CD (remember, it is shareware) will open these files.

In some cases to adhere to the ISO9660 format the .tar extension was removed. When we tarred the files then gzip the tar archive the name of the file became *File.tgz*. This name does not follow the 8.3 naming convention of the ISO9660 format. On Windows and Mac Platforms Winzip and Stuffit Expander handles this just fine. When they expand the *File.gz* the expanded file becomes *File.tar*, which both software packages can handle. On Unix platforms gunzip expands *File.tgz* but it does not append the .tar extension. So you may not recognize the file as a tar archive, but OS does recognize it as a tar archive. If you use the file command it will return saying it is a tar file. The below tar command will un-archive the file just fine.

***IMPORTANT: Read the last section in this document, Acquisition Problems and Events, for important information that may affect the processing of this data.***

## Archive Data Extraction

It is often useful to know exactly how an archive was produced when expanding its contents. Tar files were created using the following commands:

```
tar cvf archive-file files-to-be-archived
```

To create a list of the files in the archive:

```
tar tvf archive-file > contents.list
```

To extract the files from the archive:

```
tar xvf archive-file file(s)-to-extract
```

G-zipped files will have a “.gz” extension on the filename. These files can be decompressed after de-archiving, using:

```
gunzip filename.gz
```

## CD Directory Structure

./ADCP: lmg0501a.tar lmg0501b1.tar lmg0501b.tar lmg0501.tar  ./CAL: CTD_CALS.pdf instrmnt.cof MET_CALS.tar SVP_CALS.tar UW_CALS.tar  ./CTD: CONFIG.XLS Graphs.tgz Process.tgz Raw.tgz scripts.tar setup.tar  ./CTD/LOGS: *.pdf  ./DRIFTERS: DriftLog.pdf  ./EVENTLOG: EVENTLOG.XLS  ./ICE: Ice.tar  ./ISOBARS: Isobars.tar  ./JGOF: lmgjgof.tar  ./MAPS: Map24.ps Map8.ps  ./MOORING: Mooring.tar  ./NUT: Nutr.tar	./Oxygen: Oxy.tar  ./PCO2: lmgpco2.tar  ./QC_PLOTS: lmgqc.tar  ./REPORT: REPORT.DOC REPORT.htm REPORT.txt  ./RVDAS: lmgnav.tar lmgtsqfl.tar lmguw.tar xrvdas.log  ./SALINITY: SAL.tar  ./SALINITY/Drake: SaltLog.pdf XBTsalts.xls  ./TCO2: TCO2Log.pdf  ./WAYPTS: 0301wpt.txt 0501wpt.txt  ./XBT: DAT.ZIP EFILES.ZIP LOG.ZIP NAV.ZIP SFILES.ZIP XBTLog.pdf	./XCTD: *.edf *.RDF XCTD_Log.pdf  ./XCTD/Drake: *.edf *.RDF XCTDLog.pdf
---	--	---

## Distribution Contents

### ADCP

*/Adcp/*

This directory contains a tar file of gentoo's proc directory, which contains a database of the averaged ping data, Matlab m-files used in processing the data, and daily graphs of the currents. For more information contact Teri Chereskin at [tchereskin@ucsd.edu](mailto:tchereskin@ucsd.edu).

### Calibration

*/Cal/*

The tar files in the Cal directory contain images of calibration sheets for each of the following systems: Sound Velocity Probe(SVP\_CALS.TAR), Meteorological System(MET\_CALS.TAR), Underway System(UW\_CALS.TAR), and CTD\_CALS.pdf.

Refer to the instrmnt.cof file along with the specific instrument calibration sheets, both located in this directory, for information on how the RVDAS data was collected and processed.

### CTD

*CTD/*

The ctd data was collected and processed on a computer running Windows 98, using Seasave Win32 – Version 5.31a and SBE Data Processing – Version 5.31a

For more information and software visit the web site at [www.seabird.com](http://www.seabird.com).

*CTD/Setup/*

In the Setup directory there is a Config file in html, excel, and text form which contain information of which sensors were used and what freq or volt they were connected to. The file also contains a table with the vertical distance in meters from the pressure port that each sensor was mounted. The distances are positive as pressure increases.

*CTD/Scripts/*

This directory contains the batch file and psu files that we used for post processing the data. The data was processed with the standard seabird processing method. This is just a preliminary processing which was done to verify that the sensors were functioning properly during the cruise. The raw data should be re-processed using the pre and post cruise sensor calibrations.

*CTD/Data/raw*

The raw.tgz file is a tar archive file that has been compressed with gzip, for more information on this see the above *Introduction* section. This archive contains the raw file collect at each CTD cast, which is represented by a set of four files containing a bottle-firing file (.bl), a configuration file (.con), a data file (.dat) and a header file (.hdr). Casts are named with the following g501SSS.ext, where g is for the LMG, 501 is the cruise 05-01, SSS is the station number. For example; the raw files associated with the Cast 1 on this cruise are: g501001.bl, g501001.con, g501001.dat, g501001.hdr. The raw data files(\*.dat) are binary files.

*CTD/Data/process*

The process.gz file is a tar archive file that has been compressed with gzip. For more information on this see the above *Introduction* section. This archive contains the processed data files for each CTD cast, the processing method used is briefly described in the above section *CTD/Scripts/*. Also see the above

section *CTD/Data/raw* for a description of the file naming convention used. Each processed cast is represented here by a set of ten files:

GXXXCCC.con	A copy of the configuration file for the cast.
GXXXCCC.cnv	The converted file for the whole cast.
GXXXCCC.ros	The rosette file that contains the scan lines for each bottle trip.
GXXXCCC.btl	The bottle file that contains the avg, standard deviation, min, and max for a select set of variables for each bottled fired during the upcast.
DGXXXCCC.cnv	The converted file for the down cast.
DGXXXCCC.asc	An ASCII formatted file for the down cast without a header.
DGXXXCCC.hdr	The header for the down cast.
UGXXXCCC.cnv	The converted file for the up cast.
UGXXXCCC.asc	An ASCII formatted file for the up cast without a header.
UGXXXCCC.hdr	The header for the up cast.

- **Cast XX** Notes.
- **Cast XX** Notes.

## Isobar Charts

/Isobars/

This directory contains GIF image files. These file are an analysis of mean sea level pressure from the National Center for Environmental Prediction's Medium Range Forecast Model. They are updated every 6 hours. Naming the convention is as follows yyjjj.hh.gif where yy is the year, jjj is the day number, and hh is the hour.

## Data and Science Report

/Report/

Copies of this report in MS Word, HTML, and text formats.

## Sitrep

/Sitrep/

Copies of the Daily Situation Report sent to the NSF and other parties during each cruise. They give an overview of ships location, weather, ice and sea conditions, and a description of scientific operations and other events that happened on each particular day, as well as updates on overall ship status.

## Salts

/SALT/



This directory contains the log sheet for the Salt sample take during the Drake Transect Sampling, also a spreadsheet containing the Salt sample and TSG comparison. These samples were analyzed with the onboard AutoSal by the MST.

## Oxygen

/OXY/

## Science

/Science/

This directory contains data and photos collected by the individual scientists.

## WAYPOINTS

/WAYPTS/

Contains the waypoint file used for the cruise; this is read by the DAS system and the selected waypoint is displayed on the CCTV system.

## QC Plots

/QC\_PLOTS/

Postscript files of data stored each day on RVDAS for quality control analysis during the cruise. There are 3 types of files, named metXXX.ps, navXXX.ps, and oceanXXX.ps, where XXX represents the Julian day. Met files are a summary of the data from the meteorological instruments, Nav files are a summary of navigational data, and Ocean files are a summary of the underway seawater and bathymetry data.

## JGOFS Data Set

/JGOF/

The JGOFS data set consists of a single file produced each day named jg<julian\_day>.dat.gz where <julian\_day> is the day the data was acquired. The “.gz” extension indicates that the individual files are compressed before archiving. The daily file consists of 22 separate columnar fields in text format, which are described below. The JGOFS data set is obtained primarily by applying calibrations to raw data and decimating to whole minute intervals. However, several fields are derived measurements from more than a single raw input. *Note: Null, unused, or unknown fields are filled with 9's in the JGOFS data.*

Additionally, 3 separate QC plots are generated daily by the ET using the JGOFS data set. These plots include TSG and Bathymetry data, meteorological data, and navigation data. The files are called ocean<julian\_day>.ps, met<julian\_day>.ps, and nav<julian\_day>.ps respectively.

Field	Data	Units
01	GMT date	dd/mm/yy
02	GMT time	hh:mm:ss
03	PCOD latitude (negative is South)	Ddd.dddd

Field	Data	Units
04	PCOD longitude (negative is West)	Ddd.dddd
05	Ships speed	Knots
06	GPS HDOP	-
07	Gyro Heading	Degrees (azimuth)
08	Course over ground	Degrees (azimuth)
09	Mast PAR	$\mu\text{Einsteins/meters}^2 \text{ sec}$
10	Sea surface temperature	$^{\circ}\text{C}$
11	Not used	-
12	Sea surface salinity	PSU
13	Sea depth (uncorrected, calc. sw sound vel. 1500 m/s)	meters
14	True wind speed (port windbird)	meters/sec
15	True wind direction (port windbird)	degrees (azimuth)
16	Ambient air temperature	$^{\circ}\text{C}$
17	Relative humidity	%
18	Barometric pressure	mBars
19	Sea surface fluorometry	volts (0-5 FSO)
20	Not used	-
21	PSP	$\text{W/m}^2$
22	PIR	$\text{W/m}^2$

## RVDAS

/rvdas/

RVDAS (Research Vessel Data Acquisition System) was developed at Lamont-Doherty Earth Observatory of Columbia University and has been used on the R/V Maurice Ewing for several years. It was adapted for use on the Nathaniel B. Palmer and her sister ship, the R/V Laurence M. Gould.

Below you will find detailed information on the data included. Be sure to read the “Significant Acquisition Events” section below for important information about data acquisition during this cruise.

### *Meteorological and Light Data*

Measurement	File ID	Collect. Status	Rate	Instrument
Air Temperature	lmet	continuous	1 sec	R. M. young 41372VC
Relative Humidity	lmet	continuous	1 sec	R. M. young 41372VC
Wind Speed/Direction	lmet	continuous	1 sec	R. M. young 5106
PIR (LW radiation)	lmet	continuous	1 sec	Eppler PIR
PSP (SW radiation)	lmet	continuous	1 sec	Eppler PSP
Photosynthetically-Available Radiation	lmet	continuous	1 sec	BSI QSR-240
Barometer	lmet	continuous	1 sec	R. M. young 61201
GUV & PUV	lguv	continuous	1 sec	GUV2511 & PUV2510

### *Navigational Data*

Measurement	File ID	Collect. Status	Rate	Instrument
Attitude GPS	lash	continuous	1 sec	Ashtec ADU-2
P-Code GPS	lpcd	civilian mode	1 sec	Trimble 20636-00SM

Gyro	lgyr	continuous	0.2 sec	Anschutz Gyro
Trimble GPS	tgps	continuous	1 sec	NT200

*Geophysical Data*

Measurement	File ID	Collect. Status	Rate	Instrument
Bathymetry	lknu	variable	Varies	Knudsen 320B/R
Net Depth Sensor	lnds	variable	~1/3 sec	Omega PX-605
DUSH 11 Winch	ld11	variable	varies	Markey DUSH 11
DUSH 5 Winch	ldu5	variable	varies	Markey DUSH 5
DUSH 4 Winch	ldu4	variable	varies	Markey DUSH 4

*Oceanographic Data*

Measurement	File ID	Collect. Status	Rate	Instrument
Salinity	ltsg	continuous	6 sec	SeaBird 21
Sea S Temperature	ltsg	continuous	6 sec	SeaBird 3-01/S
Fluorometry (analog)	ltsg	continuous	6 sec	Turner 10-AU-005
ADCP	ladc	continuous	1 sec	RD Instruments
Oxygen	loxy	continuous	10 sec	

## Data File Names and Structures

RVDAS data is divided into two broad categories, **Underway** and **Navigation**. The groups are abbreviated “uw” and “nav”. Thus, these two tar files, lmguw.tar and lmgnav.tar exist under the top-level rvdas directory. The instruments are broken down as shown. Each data file is g-zipped to save space on the distribution. Not all data types are collected everyday or on every cruise.

RVDAS data files are named following the convention: LMG[FileID].dDDD.

- The FileID is a 4-character code representing the system being logged, for example: lmet (for meteorology)
- DDD is the Julian day of the data collection

Underway Data	File ID	Navigation Data	File ID
Meteorological	lmet	Gyro Compass	lgyr
Knudsen	lknu	P-CODE GPS	lpcd
Thermosalinograph	ltsg	Ashtech ADU2 GPS	lash
ADCP	ladc	Trimble NT2100 GPS	tgps
Sound Velocity Probe	lsvp		
GUV & PUV	lguv		
PCO2 System	lpcd		
Oxygen	loxy		

Data is received by the RVDAS system via RS-232 serial connections. The data files that comprise the rvdas data set are described below. A time tag is added to each line of data received and the data is written to disk.

YY+DDD:HH:MM:SS.SSS [data stream from instrument]

Where, YY: two-digit year, DDD: Julian Day, HH: 2 digit hours, MM: 2 digit minutes SS.SSS: seconds. All times are UTC.

The delimiters used to separate fields in the raw data files are usually spaces and commas, but other delimiters are used (::, =, @) and occasionally there is no delimiter. Care should be taken when reprocessing the data that the fields separations are clearly understood. An example data

### lknu

99+099:00:18:19.775 hf,305.2,lf,304.3

Field	Data	Units
1	RVDAS Time Tag	
2	hf – high frequency flag (12 kHz)	
3	high frequency depth	meters
4	lf – low frequency flag (3.5 kHz)	
5	low frequency depth	meters

### Inds

99+099:00:18:19.775 V01 00199.8

Field	Data	Units
1	RVDAS Time Tag	
2	V01 – Sensor 1	label
3	Depth	meters

### lmet

02+314:23:59:50.067 01.2 047 028 01.3 063 042 0988.8 001.7 084 -000.2192 0000.9358 0025.5875

Field	Data	Units
1	RVDAS Time Tag	
2	Port Wind Speed	m/s
3	Port Wind Direction	deg
4	Port Wind Direction (standard deviation)	deg
5	Starboard Wind Speed	m/s
6	Starboard Wind Direction	deg
7	Starboard Wind Direction (standard deviation)	deg
8	Barometer	millibars
9	Temperature	°C
10	Relative humidity	%
11	PSP (long wave radiometer)	Volts
12	PIR (short wave radiometer)	Volts
13	PAR (photo-synthetically available radiation, 400 - 700 nm)	Volts

Throughout the voyage there were ongoing intermittent barometer problems. Water would freeze in the barometer drain tube, causing readings approximately 10mB higher than actual barometric pressure. These anomalies usually were characterized by sharp steps in pressure reading, and are thus fairly easy to spot in the data.

## Itsg

For further information on this data, check on [www.seabird.com](http://www.seabird.com) on SBE 21 Thermosalinograph

04+321:00:01:23.978 06D572EC1801D80DE4

04+321:00:01:23.978 ttttccccrrrrr0uuu

Field	Data	Units
1	RVDAS Time Tag	
2	Internal water temperature – tttt	Hex Value
3	Conductivity - cccc	Hex Value
4	External water temperature - rrrrr	Hex Value
5	Transmissometer signal - vvv	Hex Value

Prior to Palmer Station, the Transmissometer input was not functioning.

## tsgfl

04+321:00:01:23.978 -00.070 -00.089 02.8042 33.75690 0.471306 4.341880

Field	Data	Units
1	RVDAS Time Tag	
2	Internal water temperature	°C
3	External water temperature	°C
4	Conductivity	S/cm
5	Salinity	PSU
6	Fluorometer signal (digital)	Volts
7	Transmissometer signal	Volts

## lpc0

For further information on this data, contact Tim Newberger at [tnewberg@ldeo.columbia.edu](mailto:tnewberg@ldeo.columbia.edu)

02+319:23:59:13.748 2002319.99851 7154.27 26.49 1033.6 325.79 6.74 329.3  
53.76 0 Equil

Field	Data	Units
-------	------	-------

Field	Data	Units
1	RVDAS Time Tag	
2	Julian date file string	Julian
3	IR voltage reading	mV
4	Cell temperature	°C
5	Barometer	millibars
6	VCO2	mL
7	Equilibrator temperature	°C
8	PCO2	millibars
9	Gas flow	mL/min
10	Solenoid position ID	number
11	Valve Position ID	number
12	Measured gas	name

## Iguv

03+354:15:56:13.346 122003 155612 -.00007 4.632E-4 8.417E-5 1.027E-4 3.824E-2 -4.492E-6 5.196E-4  
 5.2E-1 2.793E-3 23.876 -.804 26.812 26.852 -1.238 3.525 .000099 2.581E1 5.058E1 1.442E1 2.73E0  
 6.136E1 1.406E-1 6.187E1 39.989

### GUV only

Field	Data	Units
1	RVDAS Time Tag	
2	GUV Computer Date	mmddyy
3	GUV Computer Time	hhmmss
4	Ed0Gnd - GUV	Volts
5	Ed0320 - GUV	μW/cm <sup>2</sup> nm
6	Ed0340 - GUV	μW/cm <sup>2</sup> nm
7	Ed0313 - GUV	μW/cm <sup>2</sup> nm
8	Ed0305 - GUV	μW/cm <sup>2</sup> nm
9	Ed0380 - GUV	μW/cm <sup>2</sup> nm
10	Ed0PAR - GUV	μE/cm <sup>2</sup> sec
11	Ed0395 - GUV	μW/cm <sup>2</sup> nm
12	Ed0Temp - GUV	°C

### GUV and PUV

Field	Data	Units
1	RVDAS Time Tag	
2	GUV Computer Date	mmddyy
3	GUV Computer Time	hhmmss
4	EdZGnd -PUV	Volts
5	EdZ305 -PUV	μW/cm <sup>2</sup> nm
6	EdZ313 -PUV	μW/cm <sup>2</sup> nm
7	EdZ320 -PUV	μW/cm <sup>2</sup> nm
8	EdZ395 -PUV	μW/cm <sup>2</sup> nm
9	EdZ340 -PUV	μW/cm <sup>2</sup> nm
10	EdZPAR -PUV	μE/cm <sup>2</sup> sec
11	LuZChl -PUV	μE/srm <sup>2</sup> sec
12	EdZ380 -PUV	μW/cm <sup>2</sup> nm
13	WTemp -PUV	°C
14	Depth -PUV	m
15	EdZTemp -PUV	°C
16	LuZTemp -PUV	°C
17	Tilt -PUV	Degrees
18	Roll -PUV	Degrees
19	Ed0Gnd - GUV	Volts
20	Ed0320 - GUV	μW/cm <sup>2</sup> nm
21	Ed0340 - GUV	μW/cm <sup>2</sup> nm
22	Ed0313 - GUV	μW/cm <sup>2</sup> nm
23	Ed0305 - GUV	μW/cm <sup>2</sup> nm
24	Ed0380 - GUV	μW/cm <sup>2</sup> nm
25	Ed0PAR - GUV	μE/cm <sup>2</sup> sec
26	Ed0395 - GUV	μW/cm <sup>2</sup> nm
27	Ed0Temp - GUV	°C

## svp1

00+348:01:59:52.128 1539.40

Field	Data	Units
1	RVDAS Time Tag	
2	Sound velocity	m/s

## ladc

00+019:23:59:59.099 \$PUHAW,UVH,-1.48,-0.51,250.6

Field	Data	Units
1	RVDAS Time Tag	
2	\$PUHAW	
3	UVH (E-W, N-S, Heading)	
4	Ship Speed relative to reference layer <sup>1</sup> velocity <sup>2</sup> , East vector	knots
5	Ship Speed relative to reference layer <sup>1</sup> velocity <sup>2</sup> , North vector	knots
6	Ship heading	degrees

<sup>1</sup>The reference layer is an average velocity measured in a number of depth “bins”. On the LMG, the bins are eight meters deep and bins 3-10 define the reference layer. Hence, the reference layer is the water column from 16-80 meters beneath the ship.

<sup>2</sup>The speed output is water velocity relative to the ship’s hull and is therefore opposite of the actual movement of the ship. For example, if the ship’s heading is due north, the North/South reference layer velocity is likely to be negative (southerly).

## lash

### ATTD: Attitude Data

01+081:00:00:00.806 \$PASHR,ATT,345605.0,165.03,+001.86,-01.96,0.0018,0.0173,0\*22

Field	Data	Units
1	RVDAS Time Tag \$PASHR	
2	ATT	
3	GPS Time sec. of the week	seconds
4	heading (rel. to true North)	degrees
5	pitch	degrees
6	roll	degrees
7	Measurement RMS error	meters
8	Baseline RMS error	meters
9	attitude reset flag	

01+081:00:00:00.966 \$GPGGA,235952.00,6051.7937,S,06030.2175,W,1,08,01.0,+00068,M,,M,,\*79

Field	Data	Units
1	RVDAS Time Tag \$GPGGA	
2	UTC time at position	hhmmss.ss
3	Latitude	ddmm.mmm
4	North (N) or South (S)	
5	Longitude	ddmm.mmm
6	East (E) or West (W)	
7	GPS quality (1=GPS 2=DGPS)	
8	Number of GPS satellites used	
9	HDOP	
10	Antenna Height	meters
11	M for Meters	
12	Geoidal height	meters
13	M for meters	

Field	Data	Units
14	age of diff. GPS data	sss
15	differential reference station ID	aaaa

## lgyr

02+315:23:59:58.194 \$PASVW,00.1,A\*1D

02+315:23:59:58.414 \$IIVHW,287.7,T,,M,,N,,K\*71

02+315:23:59:58.616 \$HEHDT,287.7,T\*25

02+315:23:59:58.821 \$HEROT,001.6,A\*2C

02+315:23:59:58.984 \$HCHDT,,T\*07

## HDT: True Heading

01+083:00:00:02.893 \$HEHDT,246.3,T\*2C

Field	Data	Units
1	RVDAS Time Tag \$HEHDT	
2	Heading XXXXX = ddd.d	degrees
3	T flag for true heading, checksum	

## ROT: Rate of Turn

01+083:00:00:03.093 \$HEROT,-006.3,A\*03

Field	Data	Units
1	RVDAS Time Tag \$HEROT	
2	Rate of turn	degrees/min
3	Status: A = data valid, checksum	

## tgps

### GGA: Global Positioning Fix Data

00+040:00:00:00.985 \$GPGGA,000003,6139.961,S,05949.422,W,1,6,001.64,-00036,M,00000,M,,

Field	Data	Units
1	RVDAS Time Tag \$GPGGA	
2	Latitude in degrees with decimal minutes	ddmm.mmm
3	North (N) or South (S)	
4	Longitude in degrees with decimal minutes	ddmm.mmm
5	East (E) or West (W)	
6	GPS quality (1=GPS 2=DGPS)	
7	Number of GPS satellites used	
8	Horizontal dilution of precision (HDOP)	
9	Antenna height above/below mean-sea-level (geoid)	meters
10	Units for antenna height (M = Meters)	
11	Geoidal Separation <sup>1</sup>	
12	Units for Geoidal Separation (M = Meters)	meters
13	Age of differential GPS data, number of seconds since last SC104 Type 1 or 9	
14	Differential reference station ID	



<sup>1</sup>Geoidal Separation: the difference between the WGS-84 earth ellipsoid and mean-sea-level (geoid). A negative value represents mean-sea-level below ellipsoid.

#### GLL: Geographic Position – Latitude/Logitude

00+040:00:00:00.065 \$GPGLL,6139.96,S,05949.42,W,000002,A

Field	Data	Units
1	RVDAS Time Tag \$GPGLL	
2	Latitude	ddmm.mmm
3	North (N) or South (S)	
4	Logitude	ddmm.mmm
5	East (E) or West (W)	
6	UTC of position	hhmmss.ss
7	Status: A = Data Valid	

#### VTG: Track Made Good and Speed over Ground

00+040:00:00:00.213 \$GPVTG,161,T,149,M,009.6,N,017.8,K

Field	Data	Units
1	RVDAS Time Tag \$GPVTG	
2	Track, degrees true	degrees
3	T flag for True	
4	Track, degrees magnetic	degrees
5	M flag for Magnetic	
6	Speed over Ground	knots
7	N flag for Knots	
8	Speed over Ground	kmhr
9	K flag for km/hr	

#### VHW: Speed Through Water and Heading

00+040:00:00:00.212 \$GPVHW,246,T,234,M,012.3,N,022.8,K

Field	Data	Units
1	RVDAS Time Tag \$GPVHW	
2	Heading, degrees True	degrees
3	T flag for True	
4	Heading, degrees Magnetic	degrees
5	M flag for Magnetic	
6	Speed through water	knots
7	N flag for Knots	
8	Speed through water	km/hr
9	K flag for km/hr	

#### ZDA: Time and Date

00+040:00:00:00.285 \$GPZDA,000002,09,02,2000,00,00

Field	Data	Units
1	RVDAS Time Tag \$GPZDA	
2	UTC time	hhmmss.ss
3	Day: 01 – 31	dd
4	Month: 01 – 12	mm

Field	Data	Units
5	Year	yyy
6	Local time zone description <sup>1</sup> , 00 +/-13 hrs	
7	Local time zone minutes description, same sign as local hours	

<sup>1</sup>Zone description is the number of whole hours added to local time to obtain GMT, values are negative for East longitudes.

#### BWC: Bearing and Distance to Waypoint

00+040:00:00:00.865 \$GPBWC,000003,6209.70,S,05824.00,W,127.2,T,115.3,M,050.1,N,014

Field	Data	Units
1	RVDAS Time Tag \$GPBWC	
2	UTC of bearing	hhmmss.ss
3	Destination waypoint latitude in degrees, decimal minutes	ddmm.mmm
4	Hemisphere Flag: N or S	
5	Destination waypoint longitude in degrees, decimal minutes	ddmm.mmm
6	Hemisphere Flag: E or W	
7	Bearing, degrees true	degrees
8	T flag for True	
9	Bearing, degrees magnetic	degrees
10	M flag for Magnetic	
11	Distance to waypoint in nautical miles	nm
12	N flag for Nautical Miles	
13	Waypoint ID	

#### lpcd

##### GGA: GPS Position Fix – Geoid/Ellipsoid

00+019:23:59:59.301 \$GPGGA,235958.409,6849.6944,S,13712.8472,W,1,06,1.2,092.4,M,047.3,M,,\*67

Field	Data	Units
1	RVDAS Time Tag \$GPGGA	
2	UTC time at position	hhmmss.sss
3	Latitude	ddmm.mmm
4	North (N) or South (S)	
5	Longitude	ddmm.mmm
6	East (E) or West (W)	
7	GPS quality (1=GPS 2=DGPS 3=P-CODE)	
8	Number of GPS satellites used	
9	HDOP	
10	Antenna Height	meters
11	M for Meters	
12	Geoidal height	meters
13	M for meters	
14	Null field	
15	Checksum	

##### GLL: GPS Latitude/Longitude

00+019:23:59:59.381 \$GPGLL,6849.6944,S,13712.8472,W,235958.409,A\*35

Field	Data	Units
-------	------	-------

Field	Data	Units
1	RVDAS Time Tag \$GPGLL	
2	Latitude	degrees
3	North or South	
4	Longitude	degrees
5	East or West	
6	UTC of position	hhmmss.sss
7	status of data (A = valid)	
8	Checksum	

## VTG: GPS Track and Ground Speed

00+019:23:59:59.382 \$GPVTG,238.7,T,182.3,M,001.8,N,003.3,K\*41

Field	Data	Units
1	RVDAS Time Tag \$GPVTG	
2	Heading	degrees
3	degrees True (T)	
4	Heading	degrees
5	degrees magnetic (M)	
6	Ship speed	knots
7	N = knots	
8	Speed	km/hr
9	Checksum	

## Ifir

04+107:16:48:02.342 0 5450 :: 4/16/04 09:44:17 = 0.632 (RAW)

Field	Data	Units
1	RVDAS Time Tag	
2	Zero Field	numeric
3	Sample Number	numeric
4	Fluorometer Date	mm/dd/yy
5	Fluorometer Time	hh:mm:ss
6	Digital output of fluorometer	Volts
7	(RAW)	

## loxy

For further information on this data, contact Tim Newberger at [tnewberg@ldeo.columbia.edu](mailto:tnewberg@ldeo.columbia.edu)

04+117:23:57:23.504 MEASUREMENT	3830	380 Oxygen:	309.95	Saturation:
83.48 Temperature:	-1.35	DPhase:	33.41	BPhase:
	0.00	BAmp:	262.09	BPot:
0.00 RawTem.:	694.92		163.00	RAmp:
04+117:23:58:23.508 MEASUREMENT	3830	380 Oxygen:	309.59	Saturation:
83.38 Temperature:	-1.35	DPhase:	33.43	BPhase:
	0.00	BAmp:	262.14	BPot:
0.00 RawTem.:	694.95		163.00	RAmp:
04+117:23:59:23.512 MEASUREMENT	3830	380 Oxygen:	309.74	Saturation:
83.43 Temperature:	-1.35	DPhase:	33.42	BPhase:
	0.00	BAmp:	262.07	BPot:
0.00 RawTem.:	694.83		163.00	RAmp:

Field	Data	Units
1	RVDAS Time Tag	
2-4	Measurement ID, Model Number, Serial Number	alphanumeric
5	Oxygen heading	text
6	Oxygen Reading	Raw numeric
7	Saturation heading	text
8	Saturation Reading	Raw numeric
9	Temperature heading	text
10	Water Temperature	°C
11	Dphase heading	text
12	Dphase	Raw numeric
13	Bphase heading	text
14	BPhase	Raw numeric
15	Rphase heading	text
16	Rphase	Raw numeric
17	Bamp heading	text
18	Bamp	Raw numeric
19	Bpot heading	text
20	Bpot	Raw numeric
21	Ramp heading	text
22	Ramp	Raw numeric
23	RawTem heading	text
24	RawTemp	Raw numeric

## LMG Sensors

### Shipboard Sensors

Sensor	Description	Serial #	Cal. Date	Status
Port Anemometer	R.M. Young 105106	WM28392	12Sep05	collected
Stbd Anemometer	R.M. Young 105106	WM28393	12Sep05	collected
Barometer	R.M. Young 61201	BP01150	8Apr05	collected
Humidity/Wet Temp	R.M. Young 41372LC	06719	15Apr04	collected
Mast PAR	BSI QSR-240P	6394 6393	24Aug04 16Jan06	Collected Collected
Pyranometer	Eppler PSP	28933F3 31701F3	21Jun05 29Nov05	Collected Collected
Pyrgeometer	Eppler PIR	28903F3 32032F3	21Jun05 07Feb06	Collected Collected
Biospherical GUV	GUV-2511	25110203113 25110805127	05Oct05 10Oct05	Collected Collected
TSG	SeaBird SBE21	3208	30Jun05	collected
TSG Remote Temp	SeaBird 3-01/S	2686	14Jun05	collected
Fluorometer	Turner 10-AU-005 Lamp: daylight 10-045, reference filter: 10-052, emission filter: 10-051, excitation filter: 10-050.	6592RTX	n/a	collected
Transmissometer	WET Labs C-Star 25cm	CST-891DR	24Aug05	collected
Bathymetry	Knudsen 320B/R	10489	n/a	collected
Net Depth	Omega PX605	41200937	n/a	<b>Not collected</b>

### CTD Sensors

Sensor	Description	Serial #	Cal. Date
Pressure Sensor	In Fish s/n 91480	43528	14Nov05
Temperature	Primary	1542	06Aug05
Temperature	Secondary	2444	22Feb06
Conductivity	Primary	1200	19Jan06
Conductivity	Secondary	0692	19Jan06
Oxygen	Primary	0179	14Jan06
Oxygen	Secondary	0181	22Feb06
Transmissometer		CST-406	03Nov05
Fluorometer		88211	10Aug05

## Acquisition and Processing Information

### Processing Specifics

Refer to the instrmnt.cof file along with the specific instrument calibration sheets, both located in the Cal/ directory of the data distribution, for information on how the RVDAS data was collected and processed.

### Errors and Events

This section lists all significant events and known problems with acquisition during this cruise including instrument failures, data acquisition system failures, and other factors affecting this data set.

Date (Julian)	Time (GMT)	Event	Location
134	02:44	Started All Data systems	@68W
142	13:08	Stopped sonars & ADCP	At Palmer Station
142	14:40	Stopped GUV to upgrade WinXP	
142	15:46	Restarted GUV	
142	19:30	Restarted sonars & ADCP	Palmer Station
145	All day	Ice buildup on blades of anemometer caused low wind readings	In the Gerlache
148	~16:45-17:15	Lab Pump seawater system down for electrical testing	N. of Anvers I.
148	20:00	Lab Pump seawater system down for plumbing repair	N. of Anvers I.
148	22:23	Fluorometer Debubbler reset after lab pump water flow settled down	N. of Anvers I.
149	00:00	ADCP decided to not talk to the DAS anymore. Since this is experimental output, no action taken.	Off Adelaide Island
154	11:20	Cleared clogged equilibrator return tube in PCO2 system	Marguerite Bay -67.77, -68.38
159	1430	Shut down sonars and seawater	@Palmer Station
159	1700	Changed all radiometers out for calibration	@Palmer Station
160	12:35	Restarted GUV computer after software upgrade to WinXP-SP2	@Palmer Station 64 46.2°S, 64 3.6°W
160		Ship power testing, lab pumps down, PCO2 LiCor did not restart until manually switched	
163	00:45	Reset Ashtec ADU-2 GPS after lock up, unsure of length of data outage	Northbound Drake Passage, 57° 36' N, 64° 09' W
164	~20:00	Stopped all Data Systems	@68W

