
Cruise LMG0801

Palmer LTER

Cruise Data Report

By Fred Stuart/Victor Shen

December 29, 2007 – February 9, 2008

Table of Contents

INTRODUCTION	1
ARCHIVE DATA EXTRACTION	2
CD DIRECTORY STRUCTURE	3
DISTRIBUTION CONTENTS	4
ADCP	4
CALIBRATION.....	4
CTD.....	4
<i>CTD/</i>	4
<i>CTD/Setup/</i>	4
<i>CTD/Scripts/</i>	4
<i>CTD/Data/raw</i>	5
<i>CTD/Data/process</i>	5
MOCNESS	ERROR! BOOKMARK NOT DEFINED.
OPTICAL PLANKTON COUNTER.....	ERROR! BOOKMARK NOT DEFINED.
ICE IMAGES	5
ISOBAR CHARTS	5
DATA AND SCIENCE REPORT	6
SITREP	ERROR! BOOKMARK NOT DEFINED.
XBT	6
XCTD	6
TCO2	6
SALTS	6
NUTRIENTS	ERROR! BOOKMARK NOT DEFINED.
OXYGEN.....	ERROR! BOOKMARK NOT DEFINED.
DRIFTERS.....	7
SCIENCE	7
MAPS	7
WAYPOINTS.....	7
QC PLOTS	7
JGOFS DATA SET	8
TSG DATA FILES.....	8
RVDAS	10
<i>Meteorological and Light Data</i>	10
<i>Navigational Data</i>	10
<i>Geophysical Data</i>	10
<i>Oceanographic Data</i>	10

DATA FILE NAMES AND STRUCTURES	12
LKNU – KNUDSEN SONAR	12
LNDS – NET DEPTH SENSOR	13
LWN1 - WINCHES	13
LMET – RM YOUNG METEOROLOGICAL	13
LMWX - CAMBELL METEROLOGICAL DAS	13
LS45 – MICROTSG, THERMOSALINOGRAPH	14
LS38 – DIGITAL REMOTE TEMPERATURE	14
LTSG - THERMOSALINOGRAPH	14
LFLR – FLUOROMETER, TURNER.....	15
LDFLR – FLUOROMETER, WETLAB ECO	15
LOXY - OXYGEN.....	15
LPCO – PCO2 SYSTEM	16
LGUV – BIOSPHERICAL GUV	16
LSVP - SOUND VELOCITY PROBE IN ADCP TRANSDUCER WELL.....	17
LADC – ADCP SPEED LOG	17
LASH – ASHTECH GPS	17
LGYR - GYRO	18
TGPS - GARMIN GPS.....	19
LPCD – TRIMBLE PCODE GPS	20
LMG SENSORS	22
SHIPBOARD SENSORS	22
CTD SENSORS	22
ACQUISITION AND PROCESSING INFORMATION	23
PROCESSING SPECIFICS.....	23
ERRORS AND EVENTS	23

Introduction

The LMG data acquisition systems continuously log data from a suite of instrumentation throughout the cruise. This document describes the format of that data and its location on the distribution CDs. It also contains important information that may affect how this data is processed such as instrument failures or other known problems with acquisition.

The data collected during this cruise is distributed on a CD-ROM written in ISO9660 level-1 format. This data format has very strict requirements on filenames and organization. However, it is readable by virtually every computing platform.

All of the data has been archived with the Unix “tar” command and/or compressed using Unix “gzip” compression. Tar files have a “.tar” extension and Gzipped files have a “.gz” extension. Tools are available on all platforms for uncompressing and de-archiving these formats. On Macintosh, Stuffit Expander with DropStuff will open a tar archive and uncompress gzipped and Unix compressed files. For Windows, WinZip, a shareware utility included on this CD (remember, it is shareware) will open these files.

In some cases to adhere to the ISO9660 format the .tar extension was removed. When we tarred the files then gzip the tar archive the name of the file became *File.tgz*. This name does not follow the 8.3 naming convention of the ISO9660 format. On Windows and Mac Platforms Winzip and Stuffit Expander handles this just fine. When they expand the *File.gz* the expanded file becomes *File.tar*, which both software packages can handle. On Unix platforms gunzip expands *File.tgz* but it does not append the .tar extension. So you may not recognize the file as a tar archive, but OS does recognize it as a tar archive. If you use the file command it will return saying it is a tar file. The below tar command will un-archive the file just fine.

IMPORTANT: Read the last section in this document, Acquisition Problems and Events, for important information that may affect the processing of this data.

Archive Data Extraction

It is often useful to know exactly how an archive was produced when expanding its contents. Tar files were created using the following commands:

```
tar -cvf archive-file files-to-be-archived
```

To create a list of the files in the archive:

```
tar -tvf archive-file > contents.list
```

To extract the files from the archive:

```
tar -xvf archive-file file(s)-to-extract
```

G-zipped files will have a “.gz” extension on the filename. These files can be decompressed after de-archiving, using:

```
gunzip filename.gz
```

CD Directory Structure

ADCP: images.tar lmg0801b.tgz lmg0801.tgz CAL: CTD_Cals.tar InstCoef.txt MET_Cals.tar SVP_CALS.tar UW_Cals.tar xrvdaslg.txt CTD: CTDlogs.tar CTDsetup.tar ctd.tar DRIFTERS: EnglDrift.pdf SoloDrift.pdf GENTOO: ASHTECH GYRO PCODE GUV: GUV.tar IMAGERY: Chloroph IceImage Modis WXImage ISOBARS: Isobars.tar	JGOF: lmgJGOF.tar MAP: Large.ps Letter.ps MOORINGS: SASSI.tar SedTrap.tar PCO2: lmgPCO2.tar QCPlots: lmgQC.tar Report: Report.DOC Report.mht Report.rtf RVDAS: lmgnav.tar lmguw.tar SALT: Drake.tar LTER.tar Science: Dinner.xls eventlog.tar LTERGrid.tar POD.tar SITREP.tar	TCO2: TCO2.pdf TRAWL: Trawls.tar TSG: lmgTSG.tar WAYPTS: LTER08.txt XBT: Drake XCTD: Drake XCTDLogs.tar XCTD.tar
---	--	---

Distribution Contents

ADCP

/Adcp/

This directory contains a tar file of gentoo's proc directory, which contains a database of the averaged ping data, Matlab m-files used in processing the data, and daily graphs of the currents. For more information contact Teri Chereskin at tchereskin@ucsd.edu.

Gentoo

/Gentoo/

This directory contains data from the ADCP processing computer Gentoo. It contains Ashtech, pcode, and gyro data for Julian day 014, 015, and 016. These were the days that the RVDAS loggers failed. January 1 on Gentoo is julian day 000 and on the RVDAS it is 001. Gentoo records its data in 2hrs long files. In the pcode directory there are 3 files lpcd.d014, lpcd.d015, and lpcd.d016, these are pcode files converted from Gentoo's format to the RVDAS format using time from the gps string. In the Gentoo data file is a string \$UNIXD it is a Timestamp. The first number in the string is the computer time as a zero-based decimal day, i.e. 0.5000000 is noon UTC on Jan 1st.

Calibration

/Cal/

The tar files in the Cal directory contain images of calibration sheets for each of the following systems: Sound Velocity Probe(SVP_CALS.TAR), Meteorological System(MET_CALS.TAR), Underway System(UW_CALS.TAR), and CTD_CALS.tar.

Refer to the InstCoef.txt file along with the specific instrument calibration sheets, both located in this directory, for information on how the RVDAS data was collected and processed.

CTD

CTD/

The ctd data was collected and processed on a computer running Windows XP, using Seasave Win32 – Version 5.31a and SBE Data Processing – Version 5.31a

For more information and software visit the web site at www.seabird.com.

CTD/Setup/

In the Setup directory there is a Config file in html, excel, and text form which contain information of which sensors where used and what freq or volt the where connected to. The file also contains a table with the vertical distance in meters from the pressure port that each sensor was mounted. The distances are positive as pressure increases.

CTD/Scripts/

This directory contains the batch file and psu files that we used for post processing the data. The data was processed with the standard seabird processing method. This is just a preliminary processing which

was done to verify that the sensors were functioning properly during the cruise. The raw data should be re-processed using the pre and post cruise sensor calibrations.

CTD/Data/raw

The raw.tgz file is a tar archive file that has been compressed with gzip, for more information on this see the above *Introduction* section. This archive contains the raw file collect at each CTD cast, which is represented by a set of four files containing a bottle-firing file (.bl), a configuration file (.con), a data file (.dat) and a header file (.hdr). Casts are named with the following g801CCC.ext, where g is for the LMG, 801 is the cruise 08-01, CCC is the cast number. For example; the raw files associated with the Cast 1 on this cruise are: g801001.bl, g801001.con, g801001.dat, g801001 .hdr. The raw data files(*.dat) are binary files.

CTD/Data/process

The process.gz file is a tar archive file that has been compressed with gzip. For more information on this see the above *Introduction* section. This archive contains the processed data files for each CTD cast, the processing method used is briefly described in the above section *CTD/Scripts/*. Also see the above section *CTD/Data/raw* for a description of the file naming convention used. Each processed cast is represented here by a set of ten files:

LMG0801.con LMG0801b.com	A copy of the configuration file for the cast. LMG0801b.con was added when an altimeter was added to the rosette for testing. It has the same values as LMG0801, but with the addition of the altimeter configuration.
G801CCC.cnv	The converted file for the whole cast.
G801CCC.ros	The rosette file that contains the scan lines for each bottle trip.
G801CCC.btl	The bottle file that contains the avg, standard deviation, min, and max for a select set of variables for each bottled fired during the upcast.
DG801CCC.cnv	The converted file for the down cast.
DG801CCC.asc	An ASCII formatted file for the down cast without a header.
DG801CCC.hdr	The header for the down cast.
UG801CCC.cnv	The converted file for the up cast.
UG801CCC.asc	An ASCII formatted file for the up cast without a header.
UG801CCC.hdr	The header for the up cast.

Ice Images

/Imagery/

This directory contains files of satellite imagery sent to the ship via email, such as Chlorophyll, Ice, Isobars, Modis, Weather.

Isobar Charts

/Isobars/

This directory contains GIF image files. These file are an analysis of mean sea level pressure from the National Center for Environmental Prediction's Medium Range Forecast Model. They are updated every 6 hours. Naming the convention is as follows yyjjj.hh.gif where yy is the year, jjj is the day number, and hh is the hour.

Data Report

/Report/

Copies of this report in MS Word, HTML, and text formats.

XBT

/XBT/Drake

Expendable Bathythermographic (XBT) "Deep Blue" probes were used to obtain water column temperature profiles. The dataset includes the following files:

dat.zip	The probe drop schedule and other configuration files.
efiles.zip	The edited data files.
log.zip	The log files for drop and GPS positioning.
nav.zip	The navigation files.
sfiles.zip	The raw data files.
*.pdf	Scanned images of the paper log sheets.

XCTD

/XCTD/

Expendable Conductivity, Temperature, and Depth (XCTD) digital probes were used to obtain water column temperature and Salinity profiles. The two files were created for each drop .RDF files contain the raw data, and the .EDF contain the exported ascii data.

TCO2

/TCO2/

This directory contains the log sheet for the TCO2 sample during the Drake Transect Sampling. For further information on this data, contact Tim Newberger at tnewberg@ldeo.columbia.edu

Trawls

/Trawls/

This directory contains two file for each trawl tow. A CSV file contain the netdepth information from the RVDAS file lnds.d###, also a graph in the postscript format. The file name are as follows netdepth_d###_e###_t##.XXX, where d### is the julian day of the cast, e### is the event number, t## is the tow number, and XXX is the extension.

Salts

/SALT/

This directory contains the log sheet for the Salt sample take during the Drake Transect Sampling, also a spreadsheet containing the Salt sample and TSG comparison. These samples were analyzed with the onboard AutoSal by the MST.

Drifters

/DRIFTERS/

This directory contains the log sheet for the drifter buoys released during the Drake Transect.

Science

/Science/

This directory contains data the event log, the Picture of the Day, the dinner list, LTER grid converter, and the weekly science report.

Maps

/Maps/

This directory contains the cruise map, two postscript files, one letter size and the other 18"x24".

WAYPOINTS

/WAYPTS/

Contains the waypoint file used for the cruise; this is read by the DAS system and the selected waypoint is displayed on the CCTV system.

QC Plots

/QC_PLOTS/

Postscript files of data stored each day on RVDAS for quality control analysis during the cruise. There are 3 types of files, named metXXX.ps, navXXX.ps, and oceanXXX.ps, where XXX is represents the Julian day. Met files are a summary of the data from the meteorological instruments, Nav files are a summary of navigational data, and Ocean files are a summary of the underway seawater and bathymetry data.

JGOFS Data Set

/JGOF/

The JGOFS data set consists of a single file produced each day named jg<julian_day>.dat.gz where <julian_day> is the day the data was acquired. The “.gz” extension indicates that the individual files are compressed before archiving. The daily file consists of 22 separate columnar fields in text format, which are described below. The JGOFS data set is obtained primarily by applying calibrations to raw data and decimating to whole minute intervals. However, several fields are derived measurements from more than a single raw input. *Note: Null, unused, or unknown fields are filled with 9's in the JGOFS data.*

Additionally, 3 separate QC plots are generated daily by the ET using the JGOFS data set. These plots include TSG and Bathymetry data, meteorological data, and navigation data. The files are called ocean<julian_day>.ps, met<julian_day>.ps, and nav<julian_day>.ps respectively.

Field	Data	Units
01	GMT date	dd/mm/yy
02	GMT time	hh:mm:ss
03	PCOD latitude (negative is South)	Ddd.dddd
04	PCOD longitude (negative is West)	Ddd.dddd
05	Ships speed	Knots
06	GPS HDOP	-
07	Gyro Heading	Degrees (azimuth)
08	Course over ground	Degrees (azimuth)
09	Mast PAR	μEinsteins/meters ² sec
10	Sea surface temperature	°C
11	Not used	-
12	Sea surface salinity	PSU
13	Sea depth (uncorrected, calc. sw sound vel. 1500 m/s)	meters
14	True wind speed (port windbird)	meters/sec
15	True wind direction (port windbird)	degrees (azimuth)
16	Ambient air temperature	°C
17	Relative humidity	%
18	Barometric pressure	mBars
19	Sea surface fluorometry	volts (0-5 FSO)
20	Not used	-
21	PSP	W/m ²
22	PIR	W/m ²

TSG Data files

/TSG/tsgfl

RVDAS processes the ltsg.d### file, using the Seabird calibration. It produces a daily tsgfl.d### file with the below fields.

04+321:00:01:23.978 -00.070 -00.089 02.8042 33.75690 0.471306 4.341880

Field	Data	Units
1	RVDAS Time Tag	
2	Internal water temperature	°C
3	External water temperature	°C

LMG01-01, PALMER LTER

Field	Data	Units
4	Conductivity	S/cm
5	Salinity	PSU
6	Transmissometer signal	Volts

RVDAS

/RVDAS/

RVDAS (Research Vessel Data Acquisition System) was developed at Lamont-Doherty Earth Observatory of Columbia University and has been used on the R/V Maurice Ewing for several years. It was adapted for use on the Nathaniel B. Palmer and her sister ship, the R/V Laurence M. Gould.

Below you will find detailed information on the data included. Be sure to read the "Significant Acquisition Events" section below for important information about data acquisition during this cruise.

Meteorological and Light Data

Measurement	File ID	Collect. Status	Rate	Instrument
Air Temperature	lmet	continuous	1 sec	R. M. young 41372VC
Relative Humidity	lmet	continuous	1 sec	R. M. young 41372VC
Wind Speed/Direction	lmet	continuous	1 sec	R. M. young 5106
PAR, (Photosynthetically-Available Radiation)	lmet	continuous	1 sec	BSI QSR-240
Barometer	lmet	continuous	1 sec	R. M. young 61201
GUV & PUV	lguv	continuous	1 sec	GUV2511 & PUV2510
PIR (LW radiation)	lmwx	continuous	1 sec	Eppler PIR
PSP (SW radiation)	lmwx	continuous	1 sec	Eppler PSP
Port Ultrasonic Wind Speed/Direction	lmwx	continuous	1 sec	Gill Wind Observer II

Navigational Data

Measurement	File ID	Collect. Status	Rate	Instrument
Attitude GPS	lash	continuous	1 sec	Ashtec ADU-2
P-Code GPS	lpcd	civilian mode	1 sec	Trimble 20636-00SM
Gyro	lgyr	continuous	0.2 sec	Anschutz Gyro
Garmin GPS	tgps	continuous	1 sec	NT200

Geophysical Data

Measurement	File ID	Collect. Status	Rate	Instrument
Bathymetry	lknu	variable	Varies	Knudsen 320B/R
Net Depth Sensor	lnds	variable	~1/3 sec	Omega PX-605
DUSH 11 Winch	lwn1	variable	varies	Markey DUSH 11
DUSH 5 Winch	lwn1	variable	varies	Markey DUSH 5
DUSH 4 Winch	lwn1	variable	varies	Markey DUSH 4

Oceanographic Data

Measurement	File ID	Collect. Status	Rate	Instrument
Salinity	ltsg	continuous	6 sec	SeaBird 21
Sea Surface Temperature	ltsg	continuous	6 sec	SeaBird 3-01/S
Salinity	ls45	continuous	1 sec	SeaBird 21
Sea Surface Temperature	ls38	continuous	1 sec	SeaBird 3-01/S
Fluorometry (digital)	lflr	continuous	1 sec	Turner 10-AU-005
Fluorometry (digital)	ldflr	continuous	1 sec	Wetlab ECO

LMG01-01, PALMER LTER

ADCP, Speed Log	ladc	continuous	1 sec	RD Instruments
Oxygen	loxy	continuous	1 sec	
PCO2	lpco2	continuous	2.5 min	

Data File Names and Structures

RVDAS data is divided into two broad categories, **Underway** and **Navigation**. The groups are abbreviated “uw” and “nav”. Thus, these two tar files, lmguw.tar and lmgnav.tar exist under the top-level rvdas directory. The instruments are broken down as shown. Each data file is g-zipped to save space on the distribution. Not all data types are collected everyday or on every cruise.

RVDAS data files are named following the convention: LMG[FileID].dDDD.

- The FileID is a 4-character code representing the system being logged, for example: lmet (for meteorology)
- DDD is the Julian day of the data collection

Underway Data	File ID	Navigation Data	File ID
Meteorological – RM Young	lmet	Gyro Compass	lgyr
Meteorological - Cambell	lmwx	P-CODE GPS	lpcd
Knudsen	lknu	Ashtech ADU2 GPS	lash
TSG - Thermosalinograph	ltsg	Garmin 17 GPS	tgps
microTSG	ls45		
Digital Remote Temperature	ls38		
Fluorometer - Turner	lfir		
Fluorometer – Wetlab ECO	ldfl		
ADCP	ladc		
Sound Velocity Probe	lsvp		
GUV & PUV	lguv		
PCO2 System	lpcd		
Oxygen	loxy		
Wet Wall Flows	lsea		
Winches: Dush4,5,&11	lwn1		
Net Depth Sensor	lnds		

Data is received by the RVDAS system via RS-232 serial connections. The data files that comprise the rvdas data set are described below. A time tag is added to each line of data received and the data is written to disk.

YY+DDD:HH:MM:SS.SSS [data stream from instrument]

Where, YY: two-digit year, DDD: Julian Day, HH: 2 digit hours, MM: 2 digit minutes SS.SSS: seconds. All times are UTC.

The delimiters used to separate fields in the raw data files are usually spaces and commas, but other delimiters are used (::, =, @) and occasionally there is no delimiter. Care should be taken when reprocessing the data that the fields separations are clearly understood. An example data

lknu – Knudsen Sonar

08+024:07:36:36.245 HF,00.00, 000,0,LF,448.9,-026,1

Field	Data	Units
1	RVDAS Time Tag	
2	HF – high frequency header (12 kHz)	
3	HF - depth to surface	meters
4	HF - Echo Strength	
5	HF – Depth Valid Flag	
6	LF – low frequency header (3.5 kHz)	
7	LF - depth to surface	meters
8	LF - Echo Strength	

LMG01-01, PALMER LTER

Field	Data	Units
9	LF – Depth Valid Flag	

Inds – Net Depth Sensor

99+099:00:18:19.775 V01 00199.8

Field	Data	Units
1	RVDAS Time Tag	
2	V01 – Sensor 1	label
3	Depth	meters

lwn1 - Winches

08+033:11:27:50.673 RD,DUSH-5,00111.63,00000000,-0000012,1938

Field	Data	Units
1	RVDAS Time Tag	
2	Record Identifier, RD=Remote Data	
3	Winch Identifier, DUSH-X where X is 4, 5, or 11	
4	Tension	lbs
5	Speed	Meters/minute
6	Payout	meters
7	Checksum	

Imet – RM Young Meteorological

08+033:22:55:38.443 6.3 194 64 6.7 194 67 989.2 2.0 87 -2.9573 -12.1841 520.0833

Field	Data	Units
1	RVDAS Time Tag	
2	Port Wind Speed	m/s
3	Port Wind Direction	deg
4	Port Wind Direction (standard deviation)	deg
5	Starboard Wind Speed	m/s
6	Starboard Wind Direction	deg
7	Starboard Wind Direction (standard deviation)	deg
8	Barometer	millibars
9	Temperature	°C
10	Relative humidity	%
11	No longer Connected - PSP (long wave radiometer)	Volts
12	No Longer Connected - PIR (short wave radiometer)	Volts
13	PAR (photo-synthetically available radiation, 400 - 700 nm)	Volts

Imwx - Cambell Meterological DAS

08+034:13:52:14.216 PUS,A,356,002.15,M,+332.28,+000.97,60,08

Field	Data	Units
1	RVDAS Time Tag	
2	PUS tag – Port UltraSonic Anemometer	
3	Unit Identification, A-Z	
4	Port Wind Direction, degrees relative to Bow	deg

LMG01-01, PALMER LTER

Field	Data	Units
5	Port Wind Speed	m/s
6	Units, M=meters per second	
7	Sound Speed	m/s
8	Sonic Temperature	°C
9	Status, 0=ok, 60=Heating Enabled & ok, Other value mean a fault	
10	Check Sum	

08+034:13:52:14.454 MET,12.22322,44.25706,-75,-25,-363.6365,2.332982,-0.08215196,278.6845,
279.2192,854.6198

Field	Data	Units
1	RVDAS Time Tag	
2	MET tag	
3	Power Supply Voltage	Volts
4	Enclosure Relative Humidity	mBars
5	Not Used – future Air Temp	
6	Not Used – future Air Relative Humidity	
7	Not Used – future PAR	
8	PSP	mVolts
9	PIR	mVolts
10	PIR Thermopile	Volts
11	PIR Case Temperature	°C
12	PIR Dome Temperature	°C
13	Barometer	mBars

Is45 – microTSG, Thermosalinograph

For further information on this data, check on www.seabird.com on SBE 45 MicroTSG Thermosalinograph

08+037:13:45:57.596 2.6470, 3.03853, 33.8129, 1459.351

Field	Data	Units
1	RVDAS Time Tag	
2	Internal water temperature	°C
3	Conductivity	S/m
4	Salinity	psu
5	Sound Velocity	m/s

Is38 – digital Remote Temperature

For further information on this data, check on www.seabird.com on SBE38 Digital Thermometer

08+037:13:47:17.841 2.2527

Field	Data	Units
1	RVDAS Time Tag	
2	External water temperature	°C

Itsg - Thermosalinograph

For further information on this data, check on www.seabird.com on SBE 21 Thermosalinograph

04+321:00:01:23.978 06D572EC1801D80DE4

04+321:00:01:23.978 ttttccccrrrrrr0uuu

LMG01-01, PALMER LTER

Field	Data	Units
1	RVDAS Time Tag	
2	Internal water temperature – tttt	Hex Value
3	Conductivity - cccc	Hex Value
4	External water temperature - rrrrrr	Hex Value
5	Transmissometer signal - vvv	Hex Value

Lflr – Fluorometer, Turner

04+107:16:48:02.342 0 5450 :: 4/16/04 09:44:17 = 0.632 (RAW)

Field	Data	Units
1	RVDAS Time Tag	
2	Zero Field	numeric
3	Sample Number	numeric
4	Fluorometer Date	mm/dd/yy
5	Fluorometer Time	hh:mm:ss
6	Digital output of fluorometer	Volts
7	(RAW)	

Idflr – Fluorometer, Wetlab ECO

08+037:13:55:08.434 99/99/99 99:99:99 0.00 2585 73 543

Field	Data	Units
1	RVDAS Time Tag	
2	Fluorometer Date	mm/dd/yy
3	Fluorometer Time	hh:mm:ss
4	Chlorophyll Signal	µg/l
5	Reference	λq
6	Counts – Chlorophyll Signal	Count
7	Thermistor	

loxy - OxygenFor further information on this data, contact Tim Newberger at tnewberg@ldeo.columbia.edu

04+117:23:57:23.504 MEASUREMENT 3830 380 Oxygen: 309.95 Saturation:
83.48 Temperature: -1.35 DPhase: 33.41 BPhase: 32.22
RPhase: 0.00 BAmp: 262.09 BPot: 163.00 RAmp:
0.00 RawTem.: 694.92

Field	Data	Units
1	RVDAS Time Tag	
2-4	Measurement ID, Model Number, Serial Number	alphanumeric
5	Oxygen heading	text
6	Oxygen Reading	Raw numeric
7	Saturation heading	text
8	Saturation Reading	Raw numeric
9	Temperature heading	text

LMG01-01, PALMER LTER

10	Water Temperature	°C
11	Dphase heading	text
12	Dphase	Raw numeric
13	Bphase heading	text
14	BPhase	Raw numeric
15	Rphase heading	text
16	Rphase	Raw numeric
17	Bamp heading	text
18	Bamp	Raw numeric
19	Bpot heading	text
20	Bpot	Raw numeric
21	Ramp heading	text
22	Ramp	Raw numeric
23	RawTem heading	text
24	RawTemp	Raw numeric

Ipco – PCO2 systemFor further information on this data, contact Tim Newberger at tnewberg@ldeo.columbia.edu02+319:23:59:13.748 2002319.99851 7154.27 26.49 1033.6 325.79 6.74 329.3
53.76 0 Equil

Field	Data	Units
1	RVDAS Time Tag	
2	Julian date file string	Julian
3	IR voltage reading	mV
4	Cell temperature	°C
5	Barometer	millibars
6	VCO2	mL
7	Equilibrator temperature	°C
8	PCO2	millibars
9	Gas flow	mL/min
10	Solenoid position ID	number
11	Valve Position ID	number
12	Measured gas	name

Lguv – Biospherical GUV08+037:14:17:59.211 020608 141758 -.000099 1.307E0 7.24E0 1.316E1 2.609E1 3.285E1 3.505E1 8.075E-
2 38.993 17.985**GUV only**

Field	Data	Units
1	RVDAS Time Tag	
2	GUV Computer Date	mmddyy
3	GUV Computer Time	hhmmss
4	Ed0Gnd - GUV	Volts
5	Ed0305 - GUV	μW/cm ² nm
6	Ed0313 - GUV	μW/cm ² nm
7	Ed0320 - GUV	μW/cm ² nm
8	Ed0340 - GUV	μW/cm ² nm
9	Ed0380 - GUV	μW/cm ² nm
10	Ed0395 - GUV	μW/cm ² nm

GUV and PUV

Field	Data	Units
1	RVDAS Time Tag	
2	GUV Computer Date	mmddyy
3	GUV Computer Time	hhmmss
4	EdZGnd -PUV	Volts
5	EdZ305 -PUV	μW/cm ² nm
6	EdZ313 -PUV	μW/cm ² nm
7	EdZ320 -PUV	μW/cm ² nm
8	EdZ395 -PUV	μW/cm ² nm
9	EdZ340 -PUV	μW/cm ² nm
10	EdZPAR -PUV	μE/cm ² sec

LMG01-01, PALMER LTER

11	Ed0PAR - GUV	$\mu\text{E}/\text{cm}^2\text{sec}$
12	Ed0Temp - GUV	$^{\circ}\text{C}$
13	Ed0VIn	Volts

11	LuZChl -PUV	$\mu\text{E}/\text{srm}^2\text{sec}$
12	EdZ380 -PUV	$\mu\text{W}/\text{cm}^2\text{nm}$
13	WTemp -PUV	$^{\circ}\text{C}$
14	Depth -PUV	m
15	EdZTemp -PUV	$^{\circ}\text{C}$
16	LuZTemp -PUV	$^{\circ}\text{C}$
17	Tilt -PUV	Degrees
18	Roll -PUV	Degrees
19	Ed0Gnd - GUV	Volts
20	Ed0305 - GUV	$\mu\text{W}/\text{cm}^2\text{nm}$
21	Ed0313 - GUV	$\mu\text{W}/\text{cm}^2\text{nm}$
22	Ed0320 - GUV	$\mu\text{W}/\text{cm}^2\text{nm}$
23	Ed0340 - GUV	$\mu\text{W}/\text{cm}^2\text{nm}$
24	Ed0380 - GUV	$\mu\text{W}/\text{cm}^2\text{nm}$
25	Ed0395 - GUV	$\mu\text{W}/\text{cm}^2\text{nm}$
26	Ed0PAR - GUV	$\mu\text{E}/\text{cm}^2\text{sec}$
27	Ed0Temp - GUV	$^{\circ}\text{C}$
28	Ed0VIn	Volts

Isvp - Sound Velocity Probe in ADCP Transducer Well

00+348:01:59:52.128 1539.40

Field	Data	Units
1	RVDAS Time Tag	
2	Sound velocity	m/s

ladc – ADCP Speed Log

00+019:23:59:59.099 \$PUHAW,UVH,-1.48,-0.51,250.6

Field	Data	Units
1	RVDAS Time Tag	
2	\$PUHAW	
3	UVH (E-W, N-S, Heading)	
4	Ship Speed relative to reference layer ¹ velocity ² , East vector	knots
5	Ship Speed relative to reference layer ¹ velocity ² , North vector	knots
6	Ship heading	degrees

¹The reference layer is an average velocity measured in a number of depth “bins”. On the LMG, the bins are eight meters deep and bins 3-10 define the reference layer. Hence, the reference layer is the water column from 16-80 meters beneath the ship.

²The speed output is water velocity relative to the ship’s hull and is therefore opposite of the actual movement of the ship. For example, if the ship’s heading is due north, the North/South reference layer velocity is likely to be negative (southerly).

lash – Ashtech GPS

ATTD: Attitude Data

01+081:00:00:00.806 \$PASHR,ATT,345605.0,165.03,+001.86,-01.96,0.0018,0.0173,0*22

Field	Data	Units
-------	------	-------

LMG01-01, PALMER LTER

Field	Data	Units
1	RVDAS Time Tag \$PASHR	
2	ATT	
3	GPS Time sec. of the week	seconds
4	heading (rel. to true North)	degrees
5	pitch	degrees
6	roll	degrees
7	Measurement RMS error	meters
8	Baseline RMS error	meters
9	attitude reset flag	

01+081:00:00:00.966 \$GPGGA,235952.00,6051.7937,S,06030.2175,W,1,08,01.0,+00068,M,,M,,*79

Field	Data	Units
1	RVDAS Time Tag \$GPGGA	
2	UTC time at position	hhmmss.ss
3	Latitude	ddmm.mmm
4	North (N) or South (S)	
5	Longitude	ddmm.mmm
6	East (E) or West (W)	
7	GPS quality (1=GPS 2=DGPS)	
8	Number of GPS satellites used	
9	HDOP	
10	Antenna Height	meters
11	M for Meters	
12	Geoidal height	meters
13	M for meters	
14	age of diff. GPS data	sss
15	differential reference station ID	aaaa

Igyr - Gyro

02+315:23:59:58.194 \$PASVW,00.1,A*1D

02+315:23:59:58.414 \$IIVHW,287.7,T,,M,,N,,K*71

02+315:23:59:58.616 \$HEHDT,287.7,T*25

02+315:23:59:58.821 \$HEROT,001.6,A*2C

02+315:23:59:58.984 \$HCHDT,,T*07

HDT: True Heading

01+083:00:00:02.893 \$HEHDT,246.3,T*2C

Field	Data	Units
1	RVDAS Time Tag \$HEHDT	
2	Heading XXXXX = ddd.d	degrees
3	T flag for true heading, checksum	

ROT: Rate of Turn

LMG01-01, PALMER LTER

01+083:00:00:03.093 \$HEROT,-006.3,A*03

Field	Data	Units
1	RVDAS Time Tag \$HEROT	
2	Rate of turn	degrees/min
3	Status: A = data valid, checksum	

tgps - Garmin GPS

GGA: Global Positioning Fix Data

08+034:12:26:06.131 \$GPGGA,122607,6446.4733,S,06403.4455,W,1,11,0.9,-193.4,M,9.7,M,,*5A

Field	Data	Units
1	RVDAS Time Tag	
2	\$GPGGA Tag	
3	UTC of position	hhmmss.ss
4	Latitude in degrees with decimal minutes	ddmm.mmm
5	North (N) or South (S)	
6	Longitude in degrees with decimal minutes	ddmm.mmm
7	East (E) or West (W)	
8	GPS quality (1=GPS 2=DGPS)	
9	Number of GPS satellites used	
10	Horizontal dilution of precision (HDOP)	
11	Antenna height above/below mean-sea-level (geoid)	meters
12	Units for antenna height (M = Meters)	
13	Geoidal Separation ¹	
14	Units for Geoidal Separation (M = Meters)	meters
15	Age of differential GPS data, number of seconds since last SC104 Type 1 or 9	
16	Differential reference station ID	

¹Geoidal Separation: the difference between the WGS-84 earth ellipsoid and mean-sea-level (geoid). A negative value represents mean-sea-level below ellipsoid.

GLL: Geographic Position – Latitude/Logitude

08+034:12:26:06.211 \$GPGLL,6446.4733,S,06403.4455,W,122607,A

Field	Data	Units
1	RVDAS Time Tag	
2	\$GPGLL Tag	
3	Latitude	ddmm.mmm
4	North (N) or South (S)	
5	Logitude	ddmm.mmm
6	East (E) or West (W)	
7	UTC of position	hhmmss.ss
8	Status: A = Data Valid, V =Data Not Valid	

VTG: Track Made Good and Speed over Ground

08+034:12:26:06.211 \$GPVTG,167,T,151,M,000.0,N,0000.0,K

Field	Data	Units
1	RVDAS Time Tag	

LMG01-01, PALMER LTER

Field	Data	Units
2	\$GPVTG Tag	
3	Track, degrees true	degrees
3	T flag for True	
4	Track, degrees magnetic	degrees
5	M flag for Magnetic	
6	Speed over Ground	knots
7	N flag for Knots	
8	Speed over Ground	kmhr
9	K flag for km/hr	

Ipcd – Trimble Pcode GPS

GGA: Global Positioning Fix Data

08+034:12:26:06.131 \$GPGGA,122607.6446.4733,S,06403.4455,W,1,11,0.9,-193.4,M,9.7,M,,*5A

Field	Data	Units
1	RVDAS Time Tag	
2	\$GPGGA Tag	
3	UTC of position	hhmmss.ss
4	Latitude in degrees with decimal minutes	ddmm.mmm
5	North (N) or South (S)	
6	Longitude in degrees with decimal minutes	ddmm.mmm
7	East (E) or West (W)	
8	GPS quality (1=GPS 2=DGPS)	
9	Number of GPS satellites used	
10	Horizontal dilution of precision (HDOP)	
11	Antenna height above/below mean-sea-level (geoid)	meters
12	Units for antenna height (M = Meters)	
13	Geoidal Separation ¹	
14	Units for Geoidal Separation (M = Meters)	meters
15	Age of differential GPS data, number of seconds since last SC104 Type 1 or 9	
16	Differential reference station ID	

¹Geoidal Separation: the difference between the WGS-84 earth ellipsoid and mean-sea-level (geoid). A negative value represents mean-sea-level below ellipsoid.

GLL: Geographic Position – Latitude/Logitude

08+034:12:26:06.211 \$GPGLL,6446.4733,S,06403.4455,W,122607,A

Field	Data	Units
1	RVDAS Time Tag	
2	\$GPGLL Tag	
3	Latitude	ddmm.mmm
4	North (N) or South (S)	
5	Logitude	ddmm.mmm
6	East (E) or West (W)	
7	UTC of position	hhmmss.ss
8	Status: A = Data Valid, V =Data Not Valid	

LMG01-01, PALMER LTER

VTG: Track Made Good and Speed over Ground

08+034:12:26:06.211 \$GPVTG,167,T,151,M,000.0,N,0000.0,K

Field	Data	Units
1	RVDAS Time Tag	
2	\$GPVTG Tag	
3	Track, degrees true	degrees
3	T flag for True	
4	Track, degrees magnetic	degrees
5	M flag for Magnetic	
6	Speed over Ground	knots
7	N flag for Knots	
8	Speed over Ground	kmhr
9	K flag for km/hr	

RMC: Recommended Minimum Specific GNSS Data

08+034:13:17:26.627 \$GPRMC,131726.605,A,6446.4820,S,06403.3075,W,000.0,094.4,030208,16.3,E

Field	Data	Units
1	RVDAS Time Tag	
2	\$GPRMC Tag	
3	UTC of position	hhmmss.ss
4	Status A = Data Valid, V = Navigation Receiver Warning	
5	Latitude in degrees with decimal minutes	ddmm.mmm
6	North (N) or South (S)	
7	Longitude in degrees with decimal minutes	ddmm.mmm
8	East (E) or West (W)	
9	Speed Over Ground, knots	knots
10	Course Over Ground, degrees True	degrees
11	Date	ddmmyy
12	Magnetic Variation, degrees E/W	degrees
13	Mode Indicator E= Estimated Mode	

LMG Sensors

Shipboard Sensors

Sensor	Description	Serial #	Cal. Date	Status
Port Anemometer	R.M. Young 105106	WM57508	1-Aug-2007	collected
Stbd Anemometer	R.M. Young 105106	WM28394	1-Aug-2007	collected
Barometer	R.M. Young 61201	BP00873	19-Oct-2005	collected
Humidity/Wet Temp	RM Young 41372LC	06719	4-Jan-2007	collected
PAR for Mast	Biosph. Inst. QSR-240P	6394	29-Aug-2006	collected
PIR	Eppley PIR	32031F3	3-Apr-2007	collected
PSP	Eppley PSP	31701F3	25-Apr-2007	collected
GUV (Mast)	Biosph. Inst. GUV-2511	25110805126	13-Nov-2006	collected
Transmissometer	WET Labs C-Star 25 cm deep	CST-891DR	20-Nov-2006	collected
Fluorometer	Turner 10AU-005-CE	6592 RTX		collected
TSG	Sea-Bird 21	2131422-3208	30-Jun-2005	collected
Remote Temp	Sea-Bird 3S	34015	11-May-2007	collected
<i>MicroTSG</i>	<i>Sea-Bird 45</i>	<i>200</i>	<i>21-Mar-2007</i>	<i>evaluation</i>
<i>Digital Remote Temp</i>	<i>Sea-Bird 38</i>	<i>0352</i>	<i>06-Jun-2007</i>	<i>evaluation</i>
<i>Fluorometer</i>	<i>WET Labs ECO-FL</i>	<i>FLRTD-399</i>	<i>20-Sep-2005</i>	<i>evaluation</i>

Note: Items in *green and italics* above are running as part of a new equipment evaluation and no claims are made as to the veracity of the data collected from them.

CTD Sensors

Sensor	Description	Serial #	Cal. Date
Pressure Sensor	In Fish s/n 1480	53952	26-Sept-06
Temperature	Primary	4573	24-Jul-07
Temperature	Secondary	2444	17-Aug-06
Conductivity	Primary	2247	19-May-06
Conductivity	Secondary	2065	19-May-06
Oxygen	Primary – Voltage 2	0181	14-Apr-06
Oxygen	Secondary – Voltage 3	0196	09-Apr-06
PAR	Voltage 7	4717	07-Sept-07
Transmissometer	Voltage 4	407DR	07-Dec-06
Fluorometer	Voltage 0	FLRTF-380	19-Apr-07

Acquisition and Processing Information

Processing Specifics

Refer to the InstCoef.txt file along with the specific instrument calibration sheets, both located in the Cal/ directory of the data distribution, for information on how the RVDAS data was collected and processed.

Errors and Events

This section lists all significant events and known problems with acquisition during this cruise including instrument failures, data acquisition system failures, and other factors affecting this data set.

Date (Julian)	Time (GMT)	Event	Location
365	00:37	Started DAS logger, SeaWater on, and UW systems	@68W
365	12:45	Start ADCP, forgot to start it at 68west.	
365	19:45	Found Fluorometer and Oxygen Seawater not flowing.	
003	12:49	Seawater off and WetWall Systems off	@ Palmer Station
003	14:48	Sonar off	@ Palmer Station
005	16:20	Left Palmer Stations	Departed Palmer Station
005	16:32	SeaWater ON	Departed Palmer Station
005	16:45	PCO2, TSGs, Fluorometer's, On	Departed Palmer Station
005	17:09	Found Gentoo locked up at 16:05	
005	17:31	Restart Gentoo, had to shut it down hard. Restarted fine	
008	15:06	ADCP speed log quit @ 6:00, Stop and Restarted recording on the ADCP. Fixed the problem	
008	23:08	Stopped GUV logging to change recording option to record every 60 seconds. This did not change the DAS recordings	
012	15:02	Adjusted PCO2 Flows, standards 3, 4, and Atmos	
012	20:30	Found Seawater not flowing through Fluorometer	
014	00:25	Started WX logger on RVDAS, should have done this @ 68W, This is the logger for Imwx# files	
015	00:18	Loggers for the Imet nd Imwx files where not writing to there files. Shared memory variables were fine. Turns out on 014 @ 4:24 the logger stopped logging. Restarted logging	
017	00:47	Turns out the lash, lpcd, tgps, lgyr, and lguv all stopped logging to on the 014 @ 4:24. Restarted logging.	

LMG01-01, PALMER LTER

019	23:53	Stopped GUV logging	
021	15:40	Seawater off, ECO doing pump maintenance, shutdown logger for Wetwell	
021	18:18	SeaWater On	
021	20:03	PCO2 Started again, run standard button was pressed	
022	18:46	Barometer tube had a little water in it	
024	2:40	Changed the Barometer Wind Guard, suspected bad	
026	00:43	Seawater to Transmissometer and Fluorometer had stop flowing	
026	20:25	Sonar Turned off	@ Rothera
028	18:00	Adjusted PCO2 Flows: Standards 5, 7, 9, and 11	
032	18:38	ADCP and Sonar turned off, for Biofish Calibrations	
032	18:43	ADCP and Sonar back on	
034	11:28	SeaWater off, PCO2 in Standard Mode, Fluorometers off	@ Palmer Station
034	11:31	TSGs off	@ Palmer Station
034	11:38	Sonar off	@ Palmer Station
036	13:28	Sonar on	Departed Palmer Station
036	13:31	SeaWater, and Fluorometer on	Departed Palmer Station
036	13:39	PCO2 system on, TSGs on	Departed Palmer Station
036	15:50	PCO2 found in Hibernate Mode, power cord came out of laptop	
039	4:52	RVDAS Logger Shutdown, Seawater off, PCO2 system in Standard Mode	@ 68 West