
LMG0503

Palmer Turnover

Cruise Data Report

By Sheldon Blackman

March 12, 2005 – March 28, 2005

Table of Contents

| | |
|--|----------|
| INTRODUCTION | 1 |
| ARCHIVE DATA EXTRACTION | 2 |
| CD DIRECTORY STRUCTURE..... | 3 |
| DISTRIBUTION CONTENTS..... | 4 |
| ADCP | 4 |
| CAL | 4 |
| ISOBAR CHARTS | 4 |
| DATA AND SCIENCE REPORT | 4 |
| XBT / XCTD | 4 |
| /XBT/..... | 4 |
| QC PLOTS | 4 |
| SALINITY | 5 |
| WAYPTS | 5 |
| JGOFS DATA SET..... | 5 |
| RVDAS | 6 |
| <i>Meteorological and Light Data</i> | 6 |
| <i>Navigational Data</i> | 6 |
| <i>Geophysical Data</i> | 6 |
| <i>Oceanographic Data</i> | 6 |
| DATA FILE NAMES AND STRUCTURES..... | 7 |
| LKNU..... | 7 |
| GEN1..... | 7 |
| LMET..... | 7 |
| LTSG..... | 8 |
| TSGFL | 8 |
| LPCO..... | 8 |
| LGUV | 9 |
| SVP1..... | 9 |
| LADC..... | 10 |
| LASH..... | 10 |
| LGYR..... | 11 |
| TGPS..... | 11 |
| LPCD..... | 13 |
| LFLR | 14 |
| LOXY..... | 14 |

| | |
|---|-----------|
| LMG SENSORS | 16 |
| SHIPBOARD SENSORS | 16 |
| ACQUISITION AND PROCESSING INFORMATION | 17 |
| PROCESSING SPECIFICS | 17 |
| ERRORS AND EVENTS | 17 |

Introduction

The LMG data acquisition systems continuously log data from a suite of instrumentation throughout the cruise. This document describes the format of that data and its location on the distribution CDs. It also contains important information that may affect how this data is processed such as instrument failures or other known problems with acquisition.

The data collected during this cruise is distributed on a CD-ROM written in ISO9660 level-1 format. This data format has very strict requirements on filenames and organization. However, it is readable by virtually every computing platform.

All of the data has been archived with the Unix “tar” command and/or compressed using Unix “gzip” compression. Tar files have a “.tar” extension and Gzipped files have a “.gz” extension. Tools are available on all platforms for uncompressing and de-archiving these formats. On Macintosh, Stuffit Expander with DropStuff will open a tar archive and uncompress gzipped and Unix compressed files. For Windows9X, WinZip, a shareware utility included on this CD (remember, it is shareware) will open these files.

In some cases to adhere to the ISO9660 format the .tar extension was removed. When we tarred the files then gzip the tar archive the name of the file became *File.tar.gz*. This name does not follow the 8.3 naming convention of the ISO9660 format. So the file was renamed, dropping the .tar extension and making the file name *File.gz*. On Windows and Mac Platforms Winzip and Stuffit Expander handles this just fine. When they expand the *File.gz* the expanded file becomes *File.tar*, which both software packages can handle. On Unix platforms gunzip expands *File.gz* but it does not append the .tar extension. So you may not recognize the file as a tar archive, but the OS does recognize it as a tar archive. If you use the file command it will return saying it is a tar file. The below tar command will unarchive the file just fine.

IMPORTANT: Read the last section in this document, Acquisition Problems and Events, for important information that may affect the processing of this data.

Archive Data Extraction

It is often useful to know exactly how an archive was produced when expanding its contents. Tar files were created using the following commands:

```
tar cvf archive-file files-to-be-archived
```

To create a list of the files in the archive:

```
tar tvf archive-file > contents.list
```

To extract the files from the archive:

```
tar xvf archive-file file(s)-to-extract
```

G-zipped files will have a “.gz” extension on the filename. These files can be decompressed after de-archiving, using:

```
gunzip filename.gz
```

CD Directory Structure

```
└── ADCP
└── CAL
    instrmnt.cof
    MET_CALS.tar
    SVP_CALS.tar
    UW_CALS.tar
└── ISOBARS
    Isobars.tar
└── JGOF
    lmgjgof.tar
└── PCO2
    lmgpc02.tar
└── QC_PLOTS
    lmgqc.tar
└── REPORT
    REPORT.DOC
    REPORT.htm
    REPORT.txt
    rvdaslog.txt
└── RVDAS
    lmgnav.tar
    lmgtsgfl.tar
    lmguw.tar
└── SALINITY
    Lmg05-03_salts.dat
    Lmg05-03_salts.xls
└── UTILITY
    MAC
        ALLADMIN
    WINDOWS
        ACROBAT
        ALLADMIN
        WINZIP
└── WAYPTS
    Waypts.txt
└── XBT
    *.edf
    *.RDF
    XBTLogSheet_LMG0503.xls
└── XCTD
    *.edf
    *.RDF
    XCTDLogSheet_LMG0503.xls
```

Distribution Contents

ADCP

/Adcp/

This directory contains a tar file of gentoo's proc directory. Which contains a database of the averaged ping data, Matlab m-files used in processing the data, and daily graphs of the currents. For more information contact Teri Chereskin at tchereskin@ucsd.edu.

CAL

/Cal/

The tar files in the Cal directory contain images of calibration sheets for each of the following systems: Sound Velocity Probe(SVP_CALS.TAR), Meteorological System(MET_CALS.TAR), Underway System(UW_CALS.TAR), and CTD_CALS.TAR.

Refer to the instrmnt.cof file along with the specific instrument calibration sheets, both located in this directory, for information on how the RVDAS data was collected and processed.

Isobar Charts

/Isobars/

This directory contains GIF image files. These file are an analysis of mean sea level pressure from the National Center for Environmental Prediction's Medium Range Forecast Model. They are updated every 6 hours. Naming the convention is as follows yyjjj.hh.gif where yy is the year, jjj is the day number, and hh is the hour.

Data and Science Report

/Report/

Copies of this report in MS Word, HTML, and text formats.

XBT / XCTD

/XBT/

Expendable Bathymetric (XBT) “Deep Blue” probes were used to obtain water column temperature profiles and XCTDs were used for occasional CTD profiles for the Southbound XBT Drake Survey. Since the Autolauncher (MK12) was not functioning, all the data was collected using the MK21 Sippican Software and the hand launcher. The .RDF files contain the raw data, and the .EDF contain the exported ascii data.

QC Plots

/QC_PLOTS/

Postscript files of data stored each day on RVDAS for quality control analysis during the cruise. There are 3 types of files, named metXXX.ps, navXXX.ps, and oceanXXX.ps, where XXX is represents the Julian day. Met files are a summary of the data from the meteorological instruments, Nav files are a

summary of navigational data, and Ocean files are a summary of the underway seawater and bathymetry data.

SALINITY

/SALINITY/

Contains data collected from CTD samples using the Autosal

WAYPTS

/WAYPTS/

Contains the waypoint file used for the cruise; this is read by the DAS system and the selected waypoint is displayed on the CCTV system.

JGOFS Data Set

/JGOF/

The JGOFS data set consists of a single file produced each day named jg<julian_day>.dat.gz where <julian_day> is the day the data was acquired. The “.gz” extension indicates that the individual files are compressed before archiving. The daily file consists of 22 separate columnar fields in text format, which are described below. The JGOFS data set is obtained primarily by applying calibrations to raw data and decimating to whole minute intervals. However, several fields are derived measurements from more than a single raw input. *Note: Null, unused, or unknown fields are filled with 9's in the JGOFS data.*

Additionally, 3 separate QC plots are generated daily by the ET using the JGOFS data set. These plots include TSG and Bathymetry data, meteorological data, and navigation data. The files are called ocean<julian_day>.ps, met<julian_day>.ps, and nav<julian_day>.ps respectively.

| Field | Data | Units |
|-------|---|-----------------------------------|
| 01 | GMT date | dd/mm/yy |
| 02 | GMT time | hh:mm:ss |
| 03 | PCOD latitude (negative is South) | Ddd.dddd |
| 04 | PCOD longitude (negative is West) | Ddd.dddd |
| 05 | Ships speed | Knots |
| 06 | GPS HDOP | - |
| 07 | Gyro Heading | Degrees (azimuth) |
| 08 | Course over ground | Degrees (azimuth) |
| 09 | Mast PAR | µEinstens/meters ² sec |
| 10 | Sea surface temperature | °C |
| 11 | Not used | - |
| 12 | Sea surface salinity | PSU |
| 13 | Sea depth (uncorrected, calc. sw sound vel. 1500 m/s) | meters |
| 14 | True wind speed (port windbird) | meters/sec |
| 15 | True wind direction (port windbird) | degrees (azimuth) |
| 16 | Ambient air temperature | °C |
| 17 | Relative humidity | % |
| 18 | Barometric pressure | mBars |
| 19 | Sea surface fluorometry | volt (0-5 FSO) |
| 20 | Not used | - |

| Field | Data | Units |
|--------------|-------------|------------------|
| 21 | PSP | W/m ² |
| 22 | PIR | W/m ² |

RVDAS

/rvdas/

RVDAS (Research Vessel Data Acquisition System) was developed at Lamont-Doherty Earth Observatory of Columbia University and has been used on the R/V Maurice Ewing for several years. It was adapted for use on the Nathaniel B. Palmer and her sister ship, the R/V Laurence M. Gould.

Below you will find detailed information on the data included. Be sure to read the “Significant Acquisition Events” section below for important information about data acquisition during this cruise.

Meteorological and Light Data

| Measurement | File ID | Collect. Status | Rate | Instrument |
|--|----------------|------------------------|-------------|---------------------|
| Air Temperature | lmet | continuous | 1 sec | R. M. young 41372VC |
| Relative Humidity | lmet | continuous | 1 sec | R. M. young 41372VC |
| Wind Speed/Direction | lmet | continuous | 1 sec | R. M. young 5106 |
| PIR (LW radiation) | lmet | continuous | 1 sec | Eppley PIR |
| PSP (SW radiation) | lmet | continuous | 1 sec | Eppley PSP |
| Photosynthetically-Available Radiation | lmet | continuous | 1 sec | BSI QSR-240 |
| Barometer | lmet | continuous | 1 sec | R. M. young 61201 |
| GUV & PUV | lguv | continuous | 1 sec | GUV2511 & PUV2510 |

Navigational Data

| Measurement | File ID | Collect. Status | Rate | Instrument |
|--------------------|----------------|------------------------|-------------|--------------------|
| Attitude GPS | lash | continuous | 1 sec | Ashtec ADU-2 |
| P-Code GPS | lpcd | civilian mode | 1 sec | Trimble 20636-00SM |
| Gyro | lgyr | continuous | 0.2 sec | Anschutz Gyro |
| Trimble GPS | tgps | continuous | 1 sec | NT200 |

Geophysical Data

| Measurement | File ID | Collect. Status | Rate | Instrument |
|--------------------|----------------|------------------------|-------------|-------------------|
| Bathymetry | lknu | variable | Varies | Knudsen 320B/R |
| Net Depth Sensor | Gen1 | variable | ~1/3 sec | |

Oceanographic Data

| Measurement | File ID | Collect. Status | Rate | Instrument |
|----------------------|----------------|------------------------|-------------|-------------------|
| Salinity | ltsg | continuous | 6 sec | SeaBird 21 |
| Sea S Temperature | ltsg | continuous | 6 sec | SeaBird 3-01/S |
| Fluorometry (analog) | ltsg | continuous | 6 sec | Turner 10-AU-005 |
| ADCP | ladc | continuous | 1 sec | RD Instruments |
| Oxygen | loxy | continuous | 10 sec | |

Data File Names and Structures

RVDAS data is divided into two broad categories, ***Underway*** and ***Navigation***. The groups are abbreviated “uw” and “nav”. Thus, these two tar files, Img uw.tar and Img nav.tar exist under the top-level rvdas directory. The instruments are broken down as shown. Each data file is g-zipped to save space on the distribution. Not all data types are collected everyday or on every cruise.

RVDAS data files are named following the convention: LMG[FileID].dDDD.

- The FileID is a 4-character code representing the system being logged, for example: lmet (for meteorology)
- DDD is the Julian day of the data collection

| Underway Data | File ID | Navigation Data | File ID |
|----------------------|---------|--------------------|---------|
| Meteorological | lmet | Gyro Compass | lgyr |
| Knudsen | lknu | P-CODE GPS | lpcd |
| Thermosalinograph | ltsg | Ashtech ADU2 GPS | lash |
| ADCP | ladc | Trimble NT2100 GPS | tgps |
| Sound Velocity Probe | lsvp | | |
| GUV & PUV | lguv | | |
| PCO2 System | lpco | | |
| Oxygen | loxy | | |

Data is received by the RVDAS system via RS-232 serial connections. The data files that comprise the rvdas data set are described below. A time tag is added to each line of data received and the data is written to disk.

YY+DDD:HH:MM:SS.SSS [data stream from instrument]

Where, YY: two-digit year, DDD: Julian Day, HH: 2 digit hours, MM: 2 digit minutes SS.SSS: seconds. All times are UTC.

The delimiters used to separate fields in the raw data files are usually spaces and commas, but other delimiters are used (::, =, @) and occasionally there is no delimiter. Care should be taken when reprocessing the data that the fields separations are clearly understood. An example data

Iknu

99+099:00:18:19.775 hf,305.2,lf,304.3

| Field | Data | Units |
|-------|-----------------------------------|--------|
| 1 | RVDAS Time Tag | |
| 2 | hf – high frequency flag (12 kHz) | |
| 3 | high frequency depth | meters |
| 4 | lf – low frequency flag (3.5 kHz) | |
| 5 | low frequency depth | meters |

Gen1

99+099:00:18:19.775 V01 00199.8

| Field | Data | Units |
|-------|----------------|--------|
| 1 | RVDAS Time Tag | |
| 2 | V01 – Sensor 1 | |
| 3 | Depth | meters |

lmet

02+314:23:59:50.067 01.2 047 028 01.3 063 042 0988.8 001.7 084 -000.2192 0000.9358 0025.5875

| Field | Data | Units |
|-------|---|-----------|
| 1 | RVDAS Time Tag | |
| 2 | Port Wind Speed | m/s |
| 3 | Port Wind Direction | deg |
| 4 | Port Wind Direction (standard deviation) | deg |
| 5 | Starboard Wind Speed | m/s |
| 6 | Starboard Wind Direction | deg |
| 7 | Starboard Wind Direction (standard deviation) | deg |
| 8 | Barometer | millibars |
| 9 | Temperature | °C |
| 10 | Relative humidity | % |
| 11 | PSP (long wave radiometer) | Volts |
| 12 | PIR (short wave radiometer) | Volts |
| 13 | PAR (photo-synthetically available radiation, 400 - 700 nm) | Volts |

ItsgFor further information on this data, check on www.seabird.com on SBE 21 Thermosalinograph

04+321:00:01:23.978 06D572EC1801D8182DE4

04+321:00:01:23.978 ttttccccrrrrrruuuvvvv

| Field | Data | Units |
|-------|-------------------------------------|-----------|
| 1 | RVDAS Time Tag | |
| 2 | Internal water temperature – tttt | Hex Value |
| 3 | Conductivity - cccc | Hex Value |
| 4 | External water temperature - rrrrrr | Hex Value |
| 5 | Fluorometer signal (analog) - uuu | Hex Value |
| 6 | Transmissometer signal - vvv | Hex Value |

tsgfl

04+321:00:01:23.978 -00.070 -00.089 02.8042 33.75690 0.471306 4.341880

| Field | Data | Units |
|-------|------------------------------|-------|
| 1 | RVDAS Time Tag | |
| 2 | Internal water temperature | °C |
| 3 | External water temperature | °C |
| 4 | Conductivity | S/cm |
| 5 | Salinity | PSU |
| 6 | Fluorometer signal (digital) | Volts |
| 7 | Transmissometer signal | Volts |

Ipc0For further information on this data, contact Tim Newberger at tnewberg@ldeo.columbia.edu02+319:23:59:13.748 2002319.99851 7154.27 26.49 1033.6 325.79 6.74 329.3
53.76 0 Equil

| Field | Data | Units |
|-------|-------------------------|-----------|
| 1 | RVDAS Time Tag | |
| 2 | Julian date file string | Julian |
| 3 | IR voltage reading | mV |
| 4 | Cell temperature | °C |
| 5 | Barometer | millibars |

| Field | Data | Units |
|-------|--------------------------|-----------|
| 6 | VCO2 | mL |
| 7 | Equilibrator temperature | °C |
| 8 | PCO2 | millibars |
| 9 | Gas flow | mL/min |
| 10 | Solenoid position ID | number |
| 11 | Valve Position ID | number |
| 12 | Measured gas | name |

lguv

03+354:15:56:13.346 122003 155612 -.00007 4.632E-4 8.417E-5 1.027E-4 3.824E-2 -4.492E-6 5.196E-4
 5.2E-1 2.793E-3 23.876 -.804 26.812 26.852 -1.238 3.525 .000099 2.581E1 5.058E1 1.442E1 2.73E0
 6.136E1 1.406E-1 6.187E1 39.989

GUV only

| Field | Data | Units |
|-------|-------------------|------------------------|
| 1 | RVDAS Time Tag | |
| 2 | GUV Computer Date | mmddyy |
| 3 | GUV Computer Time | hhmmss |
| 4 | Ed0Gnd - GUV | Volts |
| 5 | Ed0320 - GUV | µW/cm ² nm |
| 6 | Ed0340 - GUV | µW/cm ² nm |
| 7 | Ed0313 - GUV | µW/cm ² nm |
| 8 | Ed0305 - GUV | µW/cm ² nm |
| 9 | Ed0380 - GUV | µW/cm ² nm |
| 10 | Ed0PAR - GUV | µE/cm ² sec |
| 11 | Ed0395 - GUV | µW/cm ² nm |
| 12 | Ed0Temp - GUV | °C |

GUV and PUV

| Field | Data | Units |
|-------|-------------------|-------------------------|
| 1 | RVDAS Time Tag | |
| 2 | GUV Computer Date | mmddyy |
| 3 | GUV Computer Time | hhmmss |
| 4 | EdZGnd -PUV | Volts |
| 5 | EdZ305 -PUV | µW/cm ² nm |
| 6 | EdZ313 -PUV | µW/cm ² nm |
| 7 | EdZ320 -PUV | µW/cm ² nm |
| 8 | EdZ395 -PUV | µW/cm ² nm |
| 9 | EdZ340 -PUV | µW/cm ² nm |
| 10 | EdZPAR -PUV | µE/cm ² sec |
| 11 | LuZChl -PUV | µE/srm ² sec |
| 12 | EdZ380 -PUV | µW/cm ² nm |
| 13 | WTemp -PUV | °C |
| 14 | Depth -PUV | m |
| 15 | EdZTemp -PUV | °C |
| 16 | LuZTemp -PUV | °C |
| 17 | Tilt -PUV | Degrees |
| 18 | Roll -PUV | Degrees |
| 19 | Ed0Gnd - GUV | Volts |
| 20 | Ed0320 - GUV | µW/cm ² nm |
| 21 | Ed0340 - GUV | µW/cm ² nm |
| 22 | Ed0313 - GUV | µW/cm ² nm |
| 23 | Ed0305 - GUV | µW/cm ² nm |
| 24 | Ed0380 - GUV | µW/cm ² nm |
| 25 | Ed0PAR - GUV | µE/cm ² sec |
| 26 | Ed0395 - GUV | µW/cm ² nm |
| 27 | Ed0Temp - GUV | °C |

svp1

00+348:01:59:52.128 1539.40

| Field | Data | Units |
|-------|----------------|-------|
| 1 | RVDAS Time Tag | |
| 2 | Sound velocity | m/s |

ladc

00+019:23:59:59.099 \$PUHAW,UVH,-1.48,-0.51,250.6

| Field | Data | Units |
|-------|--|-------------------------|
| 1 | RVDAS Time Tag | |
| 2 | \$PUHAW | |
| 3 | UVH (E-W, N-S, Heading) | |
| 4 | Ship Speed relative to reference layer ¹ velocity ² , East vector | nautical miles per hour |
| 5 | Ship Speed relative to reference layer ¹ velocity ² , North vector | nautical miles per hour |
| 6 | Ship heading | degrees |

¹The reference layer is an average velocity measured in a number of depth “bins”. On the LMG, the bins are eight meters deep and bins 3-10 define the reference layer. Hence, the reference layer is the water column from 16-80 meters beneath the ship.

²The speed output is water velocity relative to the ship’s hull and is therefore opposite of the actual movement of the ship. For example, if the ship’s heading is due north, the North/South reference layer velocity is likely to be negative (southerly).

lash

ATTD: Attitude Data

01+081:00:00:00.806 \$PASHR,ATT,345605.0,165.03,+001.86,-01.96,0.0018,0.0173,0*22

| Field | Data | Units |
|-------|------------------------------|---------|
| 1 | RVDAS Time Tag \$PASHR | |
| 2 | ATT | |
| 3 | GPS Time sec. of the week | seconds |
| 4 | heading (rel. to true North) | degrees |
| 5 | pitch | degrees |
| 6 | roll | degrees |
| 7 | Measurement RMS error | meters |
| 8 | Baseline RMS error | meters |
| 9 | attitude reset flag | |

01+081:00:00:00.966 \$GPGGA,235952.00,6051.7937,S,06030.2175,W,1,08,01.0,+00068,M,,M,,*79

| Field | Data | Units |
|-------|-----------------------------------|-----------|
| 1 | RVDAS Time Tag \$GPGGA | |
| 2 | UTC time at position | hhmmss.ss |
| 3 | Latitude | ddmm.mmm |
| 4 | North (N) or South (S) | |
| 5 | Longitude | ddmm.mmm |
| 6 | East (E) or West (W) | |
| 7 | GPS quality (1=GPS 2=DGPS) | |
| 8 | Number of GPS satellites used | |
| 9 | HDOP | |
| 10 | Antenna Height | meters |
| 11 | M for Meters | |
| 12 | Geoidal height | meters |
| 13 | M for meters | |
| 14 | age of diff. GPS data | sss |
| 15 | differential reference station ID | aaaa |

lgyr

02+315:23:59:58.194 \$PASVW,00.1,A*1D
 02+315:23:59:58.414 \$IIVHW,287.7,T,,M,,N,,K*71
 02+315:23:59:58.616 \$HEHDT,287.7,T*25
 02+315:23:59:58.821 \$HEROT,001.6,A*2C
 02+315:23:59:58.984 \$HCHDT,,T*07

HDT: True Heading

01+083:00:00:02.893 \$HEHDT,246.3,T*2C

| Field | Data | Units |
|-------|-----------------------------------|---------|
| 1 | RVDAS Time Tag \$HEHDT | |
| 2 | Heading XXXXX = ddd.d | degrees |
| 3 | T flag for true heading, checksum | |

ROT: Rate of Turn

01+083:00:00:03.093 \$HEROT,-006.3,A*03

| Field | Data | Units |
|-------|----------------------------------|-------------|
| 1 | RVDAS Time Tag \$HEROT | |
| 2 | Rate of turn | degrees/min |
| 3 | Status: A = data valid, checksum | |

tgps**GGA: Global Positioning Fix Data**

00+040:00:00:00.985 \$GPGGA,000003,6139.961,S,05949.422,W,1,6,001.64,-00036,M,00000,M,,

| Field | Data | Units |
|-------|--|----------|
| 1 | RVDAS Time Tag \$GPGGA | |
| 2 | Latitude in degrees with decimal minutes | ddmm.mmm |
| 3 | North (N) or South (S) | |
| 4 | Longitude in degrees with decimal minutes | ddmm.mmm |
| 5 | East (E) or West (W) | |
| 6 | GPS quality (1=GPS 2=DGPS) | |
| 7 | Number of GPS satellites used | |
| 8 | Horizontal dilution of precision (HDOP) | |
| 9 | Antenna height above/below mean-sea-level (geoid) | meters |
| 10 | Units for antenna height (M = Meters) | |
| 11 | Geoidal Separation ¹ | |
| 12 | Units for Geoidal Separation (M = Meters) | meters |
| 13 | Age of differential GPS data, number of seconds since last SC104 Type 1 or 9 | |
| 14 | Differential reference station ID | |

¹Geoidal Separation: the difference between the WGS-84 earth ellipsoid and mean-sea-level (geoid). A negative value represents mean-sea-level below ellipsoid.

GLL: Geographic Position – Latitude/Logitude

00+040:00:00:00.065 \$GPGLL,6139.96,S,05949.42,W,000002,A

| Field | Data | Units |
|--------------|------------------------|--------------|
| 1 | RVDAS Time Tag \$GPGLL | |
| 2 | Latitude | ddmm.mmm |
| 3 | North (N) or South (S) | |
| 4 | Longitude | ddmm.mmm |
| 5 | East (E) or West (W) | |
| 6 | UTC of position | hhmmss.ss |
| 7 | Status: A = Data Valid | |

VTG: Track Made Good and Speed over Ground

00+040:00:00:00.213 \$GPVTG,161,T,149,M,009.6,N,017.8,K

| Field | Data | Units |
|--------------|-------------------------|--------------|
| 1 | RVDAS Time Tag \$GPVTG | |
| 2 | Track, degrees true | degrees |
| 3 | T flag for True | |
| 4 | Track, degrees magnetic | degrees |
| 5 | M flag for Magnetic | |
| 6 | Speed over Ground | knots |
| 7 | N flag for Knots | |
| 8 | Speed over Ground | kmhr |
| 9 | K flag for km/hr | |

VHW: Speed Through Water and Heading

00+040:00:00:00.212 \$GPVHW,246,T,234,M,012.3,N,022.8,K

| Field | Data | Units |
|--------------|---------------------------|--------------|
| 1 | RVDAS Time Tag \$GPVHW | |
| 2 | Heading, degrees True | degrees |
| 3 | T flag for True | |
| 4 | Heading, degrees Magnetic | degrees |
| 5 | M flag for Magnetic | |
| 6 | Speed through water | knots |
| 7 | N flag for Knots | |
| 8 | Speed through water | km/hr |
| 9 | K flag for km/hr | |

ZDA: Time and Date

00+040:00:00:00.285 \$GPZDA,000002,09,02,2000,00,00

| Field | Data | Units |
|--------------|---|--------------|
| 1 | RVDAS Time Tag \$GPZDA | |
| 2 | UTC time | hhmmss.ss |
| 3 | Day: 01 – 31 | dd |
| 4 | Month: 01 – 12 | mm |
| 5 | Year | yyy |
| 6 | Local time zone description ¹ , 00 +/-13 hrs | |
| 7 | Local time zone minutes description, same sign as local hours | |

¹Zone description is the number of whole hours added to local time to obtain GMT, values are negative for East longitudes.

BWC: Bearing and Distance to Waypoint

00+040:00:00:00.865 \$GPBWC,000003,6209.70,S,05824.00,W,127.2,T,115.3,M,050.1,N,014

| Field | Data | Units |
|-------|--|-----------|
| 1 | RVDAS Time Tag \$GPBWC | |
| 2 | UTC of bearing | hhmmss.ss |
| 3 | Destination waypoint latitude in degrees, decimal minutes | ddmm.mmm |
| 4 | Hemisphere Flag: N or S | |
| 5 | Destination waypoint longitude in degrees, decimal minutes | ddmm.mmm |
| 6 | Hemisphere Flag: E or W | |
| 7 | Bearing, degrees true | degrees |
| 8 | T flag for True | |
| 9 | Bearing, degrees magnetic | degrees |
| 10 | M flag for Magnetic | |
| 11 | Distance to waypoint in nautical miles | nm |
| 12 | N flag for Nautical Miles | |
| 13 | Waypoint ID | |

Ipcd

GGA: GPS Position Fix – Geoid/Ellipsoid

00+019:23:59:59.301 \$GPGGA,235958.409,6849.6944,S,13712.8472,W,1,06,1.2,092.4,M,047.3,M,,,*67

| Field | Data | Units |
|-------|-------------------------------------|-----------|
| 1 | RVDAS Time Tag \$GPGGA | |
| 2 | UTC time at position | hhmmsssss |
| 3 | Latitude | ddmm.mmm |
| 4 | North (N) or South (S) | |
| 5 | Longitude | ddmm.mmm |
| 6 | East (E) or West (W) | |
| 7 | GPS quality (1=GPS 2=DGPS 3=P-CODE) | |
| 8 | Number of GPS satellites used | |
| 9 | HDOP | |
| 10 | Antenna Height | meters |
| 11 | M for Meters | |
| 12 | Geoidal height | meters |
| 13 | M for meters | |
| 14 | Null field | |
| 15 | Checksum | |

GLL: GPS Latitude/Longitude

00+019:23:59:59.381 \$GPGLL,6849.6944,S,13712.8472,W,235958.409,A*35

| Field | Data | Units |
|-------|------------------------|---------|
| 1 | RVDAS Time Tag \$GPGLL | |
| 2 | Latitude | degrees |
| 3 | North or South | |
| 4 | Longitude | degrees |

| Field | Data | Units |
|-------|----------------------------|------------|
| 5 | East or West | |
| 6 | UTC of position | hhmmss.sss |
| 7 | status of data (A = valid) | |
| 8 | Checksum | |

VTG: GPS Track and Ground Speed

00+019:23:59:59.382 \$GPVTG,238.7,T,182.3,M,001.8,N,003.3,K*41

| Field | Data | Units |
|-------|------------------------|---------|
| 1 | RVDAS Time Tag \$GPVTG | |
| 2 | Heading | degrees |
| 3 | degrees True (T) | |
| 4 | Heading | degrees |
| 5 | degrees magnetic (M) | |
| 6 | Ship speed | knots |
| 7 | N = knots | |
| 8 | Speed | km/hr |
| 9 | Checksum | |

Iflr

04+107:16:48:02.342 0 5450 :: 4/16/04 09:44:17 = 0.632 (RAW)

| Field | Data | Units |
|-------|-------------------------------|----------|
| 1 | RVDAS Time Tag | |
| 2 | Zero Field | numeric |
| 3 | Sample Number | numeric |
| 4 | Fluorometer Date | mm/dd/yy |
| 5 | Fluorometer Time | hh:mm:ss |
| 6 | Digital output of fluorometer | Volts |
| 7 | (RAW) | |

loxyFor further information on this data, contact Tim Newberger at tnewberg@ldeo.columbia.edu

```

04+117:23:57:23.504 MEASUREMENT      3830    380 Oxygen:        309.95   Saturation:
83.48  Temperature:     -1.35    DPhase:       33.41    BPhase:        32.22
          RPhase:        0.00    BAmp:        262.09    BPot:        163.00    RAmp:
0.00   RawTem.:       694.92
04+117:23:58:23.508 MEASUREMENT      3830    380 Oxygen:        309.59   Saturation:
83.38  Temperature:     -1.35    DPhase:       33.43    BPhase:        32.23
          RPhase:        0.00    BAmp:        262.14    BPot:        163.00    RAmp:
0.00   RawTem.:       694.95
04+117:23:59:23.512 MEASUREMENT      3830    380 Oxygen:        309.74   Saturation:
83.43  Temperature:     -1.35    DPhase:       33.42    BPhase:        32.22
          RPhase:        0.00    BAmp:        262.07    BPot:        163.00    RAmp:
0.00   RawTem.:       694.83

```

| Field | Data | Units |
|-------|---|--------------|
| 1 | RVDAS Time Tag | |
| 2-4 | Measurement ID, Model Number, Serial Number | alphanumeric |

| | | |
|----|---------------------|-------------|
| 5 | Oxygen heading | text |
| 6 | Oxygen Reading | Raw numeric |
| 7 | Saturation heading | text |
| 8 | Saturation Reading | Raw numeric |
| 9 | Temperature heading | text |
| 10 | Water Temperature | °C |
| 11 | Dphase heading | text |
| 12 | Dphase | Raw numeric |
| 13 | Bphase heading | text |
| 14 | BPhase | Raw numeric |
| 15 | Rphase heading | text |
| 16 | Rphase | Raw numeric |
| 17 | Bamp heading | text |
| 18 | Bamp | Raw numeric |
| 19 | Bpot heading | text |
| 20 | Bpot | Raw numeric |
| 21 | Ramp heading | text |
| 22 | Ramp | Raw numeric |
| 23 | RawTem heading | text |
| 24 | RawTemp | Raw numeric |

LMG Sensors

Shipboard Sensors

| Sensor | Description | Serial # | Cal. Date | Status |
|-------------------|--|-----------|-----------|-----------|
| Port Anemometer | R.M. Young 105106 | WM28394 | 16-Oct-04 | collected |
| Stbd Anemometer | R.M. Young 105106 | WM5708 | 16-Oct-04 | collected |
| Barometer | R.M. Young 61201 | BP00873 | 02-Oct-03 | collected |
| Humidity/Wet Temp | R.M. Young 41372LC | 06718 | 18-Nov-04 | collected |
| Mast PAR | BSI QSR-240P | 6393 | 12-Dec-03 | collected |
| Pyranometer | Eppley PSP | 28933F3 | 30-Mar-04 | collected |
| Pyrgeometer | Eppley PIR | 28903F3 | 30-Mar-04 | collected |
| TSG | SeaBird SBE21 | 3208 | 15-Apr-04 | collected |
| TSG Remote Temp | SeaBird 3-01/S | 1620 | 5-May-04 | collected |
| Fluorometer | Turner 10-AU-005 Lamp: daylight 10-045, reference filter: 10-052, emission filter: 10-051, excitation filter: 10-050. | 6592RTX | n/a | collected |
| Transmissometer | WET Labs C-Star 25cm | CST-830DR | 31-Jul-04 | collected |
| P-Code GPS | Trimble 20636-00 (SM) | 220035265 | n/a | collected |
| Bathymetry | Knudsen 320B/R | | n/a | collected |

Acquisition and Processing Information

Processing Specifics

Refer to the instrmnt.cof file along with the specific instrument calibration sheets, both located in the Cal/ directory of the data distribution, for information on how the RVDAS data was collected and processed.

Errors and Events

This section lists all significant events and known problems with acquisition during this cruise including instrument failures, data acquisition system failures, and other factors affecting this data set.

| Date (Julian) | Time (GMT) | Event | Location |
|---------------|------------|--|------------------|
| 074 | 1345 | Departed dock | Punta Arenas |
| 075 | 0417 | RVDAS new cruise start | |
| 075 | 0417 | Started all U/W Loggers | 68 W data limit |
| 078 | 1734 | Arrived dock, stopped all loggers except Met / Nav | Palmer Station |
| 083 | 1355 | Departed dock, started all loggers | Palmer Station |
| 083 | 1445 | TSG failure – Failed Power Supply | Neumeyer Channel |
| 083 | 1759 | Repaired TSG -Restarted TSG | Neumeyer Channel |
| 086 | 1156 | UPS Power Failure | Drake Passage |
| 086 | 1157 | Restarted all loggers | Drake Passage |
| 087 | 0312 | Stopped All Loggers | 68 W data limit |
| 088 | 1500 | Arrived Dock | Punta Arenas |
| | | | |
| | | | |