

DEPLOYMENT INSTRUCTIONS
SVP AND SVP-BAROMETER DRIFTERS

- 1) Remove the buoys from the shipping container. Remove **ONLY** the plastic shrink-wrap.
- 2) **DO NOT** remove paper tape securing the drogue and tether. **DO NOT** remove cardboard surrounding the float.

DANGER: **DO NOT** remove the paper tape securing the tether or drogue. If you do, the drogue and/or tether can unfurl during deployment and cause injury!!!

- 3) Record the five-digit ID number of the drifter. This number can be found on the shipping container, the plastic shrink-wrap or the protective cardboard box. It is also inscribed on the surface float.
- 4) Remove the activation magnet from the drifter. This magnet is now a souvenir to remind you of your very first drift buoy deployment!
- 5) Throw the buoy from the stern, lowest possible deck (preferably less than 10 meters including heave), into the sea. The ship may be traveling between 2 - 25 knots. The tether and drogue are secured with paper tape that will dissolve in the water.
- 6) Record the date, time (GMT) and location of deployment as well as the five digit ID, and send this information to the Global Drifter Program.

Thank you very much!

CONTACT PERSON:

Shaun Dolk, Global Drifter Program
 NOAA/AOML/PhOD
 4301 Rickenbacker Cswy
 Miami, FL 33149, USA
 Tel: 305-361-4546 Fax: 305-361-4439
 E-mail: Shaun.Dolk@noaa.gov

Web site: http://www.aoml.noaa.gov/phod/dac/dep_form.html.

Sample log sheet

ID	Date	Time (GMT)	Latitude	Longitude
xxxxx	mm/dd/yy	hh:mm	DD mm.mm N/S	DDD mm.mm E/W
132702	DEC 16, 2016	12:58	59° 59.85' S	58° 08.37' W
_____	___/___/___	___:___	_____	_____
_____	___/___/___	___:___	_____	_____
_____	___/___/___	___:___	_____	_____